Ref: 01103

Serie IP44 Low voltage

IP44 Low-voltage

IP44 Wander plug 3P+N+E 57/100 75/130V 16A 4H



Features

Application:	Electrical connection
Suitable for outdoor installation:	No
Type of installation:	Mobile
Rated current (A):	16
Voltage (V):	57/100-75/130
Frequency (Hz):	50/60
Poles:	3P+N+E
Clock position:	4
Color:	Yellow

Technical data

Protection degree:	IP44
Resistance to impact:	IK08
Glow wire resistance (ºC):	960
Ball pressure test (°C):	125

Additional features

Flexible cable (mm²):	1-2,5
Connection angle:	Straight
Phase Inverter:	No

Ref: 01103

Materials

Material of plastic parts:	Polyamide 6
Contact Material:	Copper-zinc alloy
Halogen-free materials:	Yes

Certificates and regulations

Directive:	2014/35/EU
Standards:	UNE-EN 60309-1; UNE-EN 60309-2; IEC 60884-1

Packaging

Supply:	Supplied in an individual box per packaging multiple
Individual Packaging Type:	Uncaged
UoM Packaging - Individual:	Unit
Minimum Selling Quantity:	10
Individual packaging dimensions - HxWxD (m):	0.025 x 0.23 x 0.135
Net weight per unit (kg):	0.182
Gross weight per unit (kg):	0.2

Codes

GTIN-13 code:	8431044011035
Tariff code:	85366990
ETIM code 9.0:	EC000140

Downloads (links)

Product drawing STP (URL):	https://ideelectric.com/docs/plans/stp/01103.stp
Product drawing DXF (URL):	https://ideelectric.com/docs/plans/dxf/01103.dxf
Product drawing (PDF):	https://ideelectric.com/docs/plans/pdf/01103.pdf
Assembly instructions:	https://assemblysteps.org/qr/