Ref: 01671

Serie IP67 Low voltage

IP67 Low-voltage

IP66-IP67 Wall plug 2P+E 100/130V 63A 4H. Pilot contact



Features

Application:	Electrical connection
Suitable for outdoor installation:	Yes
Type of installation:	Wall-mounted
Rated current (A):	63
Voltage (V):	100/130
Frequency (Hz):	50/60
Poles:	2P+E
Clock position:	4
Color:	Yellow

Technical data

Protection degree:	IP66-IP67
Resistance to impact:	IK08
Glow wire resistance (ºC):	960
Ball pressure test (°C):	125

Additional features

Flexible cable (mm²):	6-16
Rigid Cable (mm²):	6-25
Connection angle:	Angled
Phase Inverter:	No

Ref: 01671

Materials

Material of plastic parts:	Polyamide 6
Contact Material:	Copper-zinc alloy
Halogen-free materials:	Yes

Certificates and regulations

Directive:	2014/35/EU
Standards:	UNE-EN 60309-1; UNE-EN 60309-2; IEC 60884-1

Packaging

Supply:	Supplied in an individual box per packaging multiple
Individual Packaging Type:	Uncaged
UoM Packaging - Individual:	Unit
Minimum Selling Quantity:	2
Individual packaging dimensions - HxWxD (m):	0.11 x 0.185 x 0.325
Net weight per unit (kg):	0.91
Gross weight per unit (kg):	1

Codes

GTIN-13 code:	8431044016719
Tariff code:	85366990
ETIM code 9.0:	EC001319

Downloads (links)

Product drawing STP (URL):	https://ideelectric.com/docs/plans/stp/01671.stp
Product drawing DXF (URL):	https://ideelectric.com/docs/plans/dxf/01671.dxf
Product drawing (PDF):	https://ideelectric.com/docs/plans/pdf/01671.pdf
Assembly instructions:	https://assemblysteps.org/qr/