Ref: 01834

Serie IP44-IP67 Interlocking

IP44-IP67 Interlocking sockets

IP66-IP67 Wall interlocking socket 2P+E 100/130V 32A 4H



Features

Application:	Electrical connection
Suitable for outdoor installation:	Yes
Type of installation:	Wall-mounted
Rated current (A):	32
Voltage (V):	100/130
Frequency (Hz):	50/60
Poles:	2P+E
Clock position:	4
Color:	Yellow

Technical data

Protection degree:	IP66-IP67
Resistance to impact:	IK08
Glow wire resistance (ºC):	960
Ball pressure test (°C):	125

Additional features

Flexible cable (mm²):	2,5-6
Rigid Cable (mm²):	2,5-10
Phase Inverter:	No

Ref: 01834

Materials

Material of plastic parts:	Polyamide 6
Contact Material:	Copper-zinc alloy
Halogen-free materials:	Yes

Certificates and regulations

Directive:	2014/35/EU
Standards:	UNE-EN 60309-1; UNE-EN 60309-2; IEC 60884-1

Packaging

Supply:	Supplied in an individual box per packaging multiple
Individual Packaging Type:	Box
UoM Packaging - Individual:	Unit
Minimum Selling Quantity:	1
Individual packaging dimensions - HxWxD (m):	0.13 x 0.104 x 0.19
Net weight per unit (kg):	0.698
Gross weight per unit (kg):	0.768

Codes

GTIN-13 code:	8431044018348
Tariff code:	85366990
ETIM code 9.0:	EC001324

Downloads (links)

Product drawing STP (URL):	https://ideelectric.com/docs/plans/stp/01834.stp
Product drawing DXF (URL):	https://ideelectric.com/docs/plans/dxf/01834.dxf
Product drawing (PDF):	https://ideelectric.com/docs/plans/pdf/01834.pdf
Assembly instructions:	https://assemblysteps.org/qr/