Ref: 02605

Serie IP67 Low voltage

IP67 Low-voltage

IP66-IP67 Wander plug 3P+E 200/250V 32A 9H



Features

Application:	Electrical connection
Suitable for outdoor installation:	Yes
Type of installation:	Mobile
Rated current (A):	32
Voltage (V):	200/250
Frequency (Hz):	50/60
Poles:	3P+E
Clock position:	9
Color:	Blue

Technical data

Protection degree:	IP66-IP67
Resistance to impact:	IK08
Glow wire resistance (ºC):	960
Ball pressure test (°C):	125

Additional features

Flexible cable (mm²):	2,5-6
Connection angle:	Straight
Phase Inverter:	No

Ref: 02605

Materials

Material of plastic parts:	Polyamide 6
Contact Material:	Copper-zinc alloy
Halogen-free materials:	Yes

Certificates and regulations

Directive:	2014/35/EU
Standards:	UNE-EN 60309-1; UNE-EN 60309-2; IEC 60884-1

Packaging

Supply:	Supplied in an individual box per packaging multiple
Individual Packaging Type:	Uncaged
UoM Packaging - Individual:	Unit
Minimum Selling Quantity:	5
Individual packaging dimensions - HxWxD (m):	0.05 x 0.23 x 0.135
Net weight per unit (kg):	0.238
Gross weight per unit (kg):	0.262

Codes

GTIN-13 code:	8431044026053
Tariff code:	85366990
ETIM code 9.0:	EC000140

Downloads (links)

Product drawing STP (URL):	https://ideelectric.com/docs/plans/stp/02605.stp
Product drawing DXF (URL):	https://ideelectric.com/docs/plans/dxf/02605.dxf
Product drawing (PDF):	https://ideelectric.com/docs/plans/pdf/02605.pdf
Assembly instructions:	https://assemblysteps.org/qr/