**Ref: 02854**

# Serie IP67 Low voltage

## IP67 Low-voltage

IP66-IP67 Sloping flush-fit socket 2P+E 200/250V 125A 6H



## Features

| | |
|---|---|
| **Application:** | Electrical connection |
| **Suitable for outdoor installation:** | Yes |
| **Type of installation:** | Recessed |
| **Rated current (A):** | 125 |
| **Voltage (V):** | 200/250 |
| **Frequency (Hz):** | 50/60 |
| **Poles:** | 2P+E |
| **Clock position:** | 6 |
| **Color:** | Blue |

## Technical data

| | |
|---|---|
| **Protection degree:** | IP66-IP67 |
| **Resistance to impact:** | IK08 |
| **Glow wire resistance (ºC):** | 960 |
| **Ball pressure test (°C):** | 125 |

## Additional features

| | |
|---|---|
| **Flexible cable (mm²):** | 16-50 |
| **Rigid Cable (mm²):** | 16-70 |
| **Connection angle:** | Angled |
| **Phase Inverter:** | No |

# Ref: 02854

## Materials

| | |
|---|---|
| **Material of plastic parts:** | Polyamide 6 |
| **Contact Material:** | Copper-zinc alloy |
| **Halogen-free materials:** | Yes |

## Certificates and regulations

| | |
|---|---|
| **Directive:** | 2014/35/EU |
| **Standards:** | UNE-EN 60309-1; UNE-EN 60309-2; IEC 60884-1 |

## Packaging

| | |
|---|---|
| **Supply:** | Supplied in an individual box per packaging multiple |
| **Individual Packaging Type:** | Uncaged |
| **UoM Packaging - Individual:** | Unit |
| **Minimum Selling Quantity:** | 2 |
| **Individual packaging dimensions - HxWxD (m):** | 0.065 x 0.185 x 0.285 |
| **Net weight per unit (kg):** | 0.865 |
| **Gross weight per unit (kg):** | 0.952 |

## Codes

| | |
|---|---|
| **GTIN-13 code:** | 8431044028545 |
| **Tariff code:** | 85366990 |
| **ETIM code 9.0:** | EC001317 |

## Downloads (links)

| | |
|---|---|
| **Assembly instructions:** | https://assemblysteps.org/qr/ |