Ref: 03116

Serie IP44 Low voltage

IP44 Low-voltage

IP44 Straight flush-fit plug 3P+N+E 200/346 240/415V 32A 6H



Features

Application:	Electrical connection
Suitable for outdoor installation:	No
Type of installation:	Recessed
Rated current (A):	32
Voltage (V):	200/346-240/415
Frequency (Hz):	50/60
Poles:	3P+N+E
Clock position:	6
Color:	Red

Technical data

Protection degree:	IP44
Resistance to impact:	IK08
Glow wire resistance (ºC):	960
Ball pressure test (°C):	125

Additional features

Flexible cable (mm²):	2,5-6
Rigid Cable (mm²):	2,5-10
Connection angle:	Straight
Phase Inverter:	No

Ref: 03116

Materials

Material of plastic parts:	Polyamide 6
Contact Material:	Copper-zinc alloy
Halogen-free materials:	Yes

Certificates and regulations

Directive:	2014/35/EU
Standards:	UNE-EN 60309-1; UNE-EN 60309-2; IEC 60884-1

Packaging

Supply:	Supplied in an individual box per packaging multiple
Individual Packaging Type:	Uncaged
UoM Packaging - Individual:	Unit
Minimum Selling Quantity:	10
Individual packaging dimensions - HxWxD (m):	0.013 x 0.185 x 0.285
Net weight per unit (kg):	0.194
Gross weight per unit (kg):	0.214

Codes

GTIN-13 code:	8431044031163
Tariff code:	85366990
ETIM code 9.0:	EC001319

Downloads (links)

Product drawing STP (URL):	https://ideelectric.com/docs/plans/stp/03116.stp
Product drawing DXF (URL):	https://ideelectric.com/docs/plans/dxf/03116.dxf
Product drawing (PDF):	https://ideelectric.com/docs/plans/pdf/03116.pdf
Assembly instructions:	https://assemblysteps.org/qr/