Ref: 03812

Serie IP44-IP67 Interlocking

IP44-IP67 Interlocking sockets

IP66-IP67 flush-fit interlocking socket 3P+E 380/415V 16A 6H



Features

Application:	Electrical connection
Suitable for outdoor installation:	Yes
Type of installation:	Recessed
Rated current (A):	16
Voltage (V):	380/415
Frequency (Hz):	50/60
Poles:	3P+E
Clock position:	6
Color:	Red

Technical data

Protection degree:	IP66-IP67
Resistance to impact:	IK08
Glow wire resistance (ºC):	960
Ball pressure test (°C):	125

Additional features

Flexible cable (mm²):	1,5-2,5
Rigid Cable (mm²):	1,5-4
Phase Inverter:	No

Ref: 03812

Materials

Material of plastic parts:	Polyamide 6
Contact Material:	Copper-zinc alloy
Halogen-free materials:	Yes

Certificates and regulations

Directive:	2014/35/EU
Standards:	UNE-EN 60309-1; UNE-EN 60309-2; IEC 60884-1

Packaging

Supply:	Supplied in an individual box per packaging multiple
Individual Packaging Type:	Box
UoM Packaging - Individual:	Unit
Minimum Selling Quantity:	1
Individual packaging dimensions - HxWxD (m):	0.13 x 0.104 x 0.19
Net weight per unit (kg):	0.584
Gross weight per unit (kg):	0.643

Codes

GTIN-13 code:	8431044038124
Tariff code:	85366990
ETIM code 9.0:	EC001324

Downloads (links)

Product drawing STP (URL):	https://ideelectric.com/docs/plans/stp/03812.stp
Product drawing DXF (URL):	https://ideelectric.com/docs/plans/dxf/03812.dxf
Product drawing (PDF):	https://ideelectric.com/docs/plans/pdf/03812.pdf
Assembly instructions:	https://assemblysteps.org/qr/