Ref: 03873

Serie IP67 Low voltage

IP67 Low-voltage

IP66-IP67 Wall socket 3P+N+E 200/346 240/415V 63A 6H



Features

Application:	Electrical connection
Suitable for outdoor installation:	Yes
Type of installation:	Wall-mounted
Rated current (A):	63
Voltage (V):	200/346-240/415
Frequency (Hz):	50/60
Poles:	3P+N+E
Clock position:	6
Color:	Red

Technical data

Protection degree:	IP66-IP67
Resistance to impact:	IK08
Glow wire resistance (ºC):	960
Ball pressure test (°C):	125

Additional features

Flexible cable (mm²):	6-16
Rigid Cable (mm²):	6-25
Connection angle:	Angled
Phase Inverter:	No

Ref: 03873

Materials

Material of plastic parts:	Polyamide 6
Contact Material:	Copper-zinc alloy
Halogen-free materials:	Yes

Certificates and regulations

Directive:	2014/35/EU
Standards:	UNE-EN 60309-1; UNE-EN 60309-2; IEC 60884-1

Packaging

Supply:	Supplied in an individual box per packaging multiple
Individual Packaging Type:	Uncaged
UoM Packaging - Individual:	Unit
Minimum Selling Quantity:	1
Individual packaging dimensions - HxWxD (m):	0.13 x 0.19 x 0.23
Net weight per unit (kg):	1.003
Gross weight per unit (kg):	1.103

Codes

GTIN-13 code:	8431044038735
Tariff code:	85366990
ETIM code 9.0:	EC001321

Downloads (links)

Product drawing STP (URL):	https://ideelectric.com/docs/plans/stp/03873.stp
Assembly instructions:	https://assemblysteps.org/qr/