Ref: 06121

Serie IP44-IP67 Extra low voltage

IP44-IP67 Extra low-voltage

IP44 Extra low voltage wall plug 2P 24/42V cc 16A 10H



Features

Application:	Electrical connection
Suitable for outdoor installation:	No
Type of installation:	Wall-mounted
Rated current (A):	16
Voltage (V):	24/42
Frequency (Hz):	cc
Poles:	2P
Clock position:	10
Color:	White

Technical data

Protection degree:	IP44
Resistance to impact:	IK08
Glow wire resistance (ºC):	960
Ball pressure test (°C):	125

Additional features

Flexible cable (mm²):	4-10
Rigid Cable (mm²):	4-10
Connection angle:	Angled
Phase Inverter:	No

Ref: 06121

Materials

Material of plastic parts:	Polyamide 6
Contact Material:	Copper-zinc alloy
Halogen-free materials:	Yes

Certificates and regulations

Directive:	2014/35/EU
Standards:	UNE-EN 60309-1; UNE-EN 60309-2; IEC 60884-1

Packaging

Supply:	Supplied in an individual box per packaging multiple
Individual Packaging Type:	Uncaged
UoM Packaging - Individual:	Unit
Minimum Selling Quantity:	10
Individual packaging dimensions - HxWxD (m):	0.022 x 0.185 x 0.285
Net weight per unit (kg):	0.198
Gross weight per unit (kg):	0.218

Codes

GTIN-13 code:	8431044061214
Tariff code:	85366990
ETIM code 9.0:	EC001319

Downloads (links)

Product drawing DXF (URL):	https://ideelectric.com/docs/plans/dxf/06121.dxf
Product drawing (PDF):	https://ideelectric.com/docs/plans/pdf/06121.pdf
Assembly instructions:	https://assemblysteps.org/qr/