Ref: 07825

Serie IP67 Low voltage

IP67 Low-voltage

IP66-IP67 Wall socket 3P+E >50V (301-500HZ) 32A 2H



Features

Application:	Electrical connection
Suitable for outdoor installation:	Yes
Type of installation:	Wall-mounted
Rated current (A):	32
Voltage (V):	>50
Frequency (Hz):	301/500
Poles:	3P+E
Clock position:	2
Color:	Green

Technical data

Protection degree:	IP66-IP67
Resistance to impact:	IK08
Glow wire resistance (ºC):	960
Ball pressure test (°C):	125

Additional features

Flexible cable (mm²):	2,5-6
Rigid Cable (mm²):	2,5-10
Connection angle:	Angled
Phase Inverter:	No

Ref: 07825

Materials

Material of plastic parts:	Polyamide 6
Contact Material:	Copper-zinc alloy
Halogen-free materials:	Yes

Certificates and regulations

Directive:	2014/35/EU
Standards:	UNE-EN 60309-1; UNE-EN 60309-2; IEC 60884-1

Packaging

Supply:	Supplied in an individual box per packaging multiple
Individual Packaging Type:	Uncaged
UoM Packaging - Individual:	Unit
Minimum Selling Quantity:	10
Net weight per unit (kg):	0.398
Gross weight per unit (kg):	0.438

Codes

GTIN-13 code:	8431044406602
Tariff code:	85366990
ETIM code 9.0:	EC001321

Downloads (links)

Assembly instructions:	https://assemblysteps.org/qr/