**Ref: 08446**

# Serie IP44-IP67 Extra low voltage

## IP44-IP67 Extra low-voltage

IP44 Extra low voltage wall plug 3P 24/42V (400HZ) 32A 3H



## Features

| | |
|---|---|
| **Application:** | Electrical connection |
| **Suitable for outdoor installation:** | No |
| **Type of installation:** | Wall-mounted |
| **Rated current (A):** | 32 |
| **Voltage (V):** | 24/42 |
| **Frequency (Hz):** | 400 |
| **Poles:** | 3P |
| **Clock position:** | 3 |
| **Color:** | Green |

## Technical data

| | |
|---|---|
| **Protection degree:** | IP44 |
| **Resistance to impact:** | IK08 |
| **Glow wire resistance (ºC):** | 960 |
| **Ball pressure test (°C):** | 125 |

## Additional features

| | |
|---|---|
| **Flexible cable (mm²):** | 4-10 |
| **Rigid Cable (mm²):** | 4-10 |
| **Connection angle:** | Angled |
| **Phase Inverter:** | No |

# Ref: 08446

## Materials

| | |
|---|---|
| **Material of plastic parts:** | Polyamide 6 |
| **Contact Material:** | Copper-zinc alloy |
| **Halogen-free materials:** | Yes |

## Certificates and regulations

| | |
|---|---|
| **Directive:** | 2014/35/EU |
| **Standards:** | UNE-EN 60309-1; UNE-EN 60309-2; IEC 60884-1 |

## Packaging

| | |
|---|---|
| **Supply:** | Supplied in an individual box per packaging multiple |
| **Individual Packaging Type:** | Uncaged |
| **UoM Packaging - Individual:** | Unit |
| **Minimum Selling Quantity:** | 6 |
| **Individual packaging dimensions - HxWxD (m):** | 0.037 x 0.185 x 0.285 |
| **Net weight per unit (kg):** | 0.032 |
| **Gross weight per unit (kg):** | 0.036 |

## Codes

| | |
|---|---|
| **GTIN-13 code:** | 8431044084466 |
| **Tariff code:** | 85366990 |
| **ETIM code 9.0:** | EC001319 |

## Downloads (links)

| | |
|---|---|
| **Product drawing DXF (URL):** | https://ideelectric.com/docs/plans/dxf/08446.dxf |
| **Product drawing (PDF):** | https://ideelectric.com/docs/plans/pdf/08446.pdf |
| **Assembly instructions:** | https://assemblysteps.org/qr/ |