**Ref: 09204**

# Serie IP44-IP67 Extra low voltage

## IP44-IP67 Extra low-voltage

IP44 Extra low voltage wander socket 2P 42V (50/60HZ) 32A 12H



## Features

| | |
|---|---|
| **Application:** | Electrical connection |
| **Suitable for outdoor installation:** | No |
| **Type of installation:** | Mobile |
| **Rated current (A):** | 32 |
| **Voltage (V):** | 42 |
| **Frequency (Hz):** | 50/60 |
| **Poles:** | 2P |
| **Clock position:** | 12 |
| **Color:** | White |

## Technical data

| | |
|---|---|
| **Protection degree:** | IP44 |
| **Resistance to impact:** | IK08 |
| **Glow wire resistance (ºC):** | 960 |
| **Ball pressure test (°C):** | 125 |

## Additional features

| | |
|---|---|
| **Flexible cable (mm²):** | 1-10 |
| **Connection angle:** | Straight |
| **Phase Inverter:** | No |

# Ref: 09204

## Materials

| | |
|---|---|
| **Material of plastic parts:** | Polyamide 6 |
| **Contact Material:** | Copper-zinc alloy |
| **Halogen-free materials:** | Yes |

## Certificates and regulations

| | |
|---|---|
| **Directive:** | 2014/35/EU |
| **Standards:** | UNE-EN 60309-1; UNE-EN 60309-2; IEC 60884-1 |

## Packaging

| | |
|---|---|
| **Supply:** | Supplied in an individual box per packaging multiple |
| **Individual Packaging Type:** | Uncaged |
| **UoM Packaging - Individual:** | Unit |
| **Minimum Selling Quantity:** | 10 |
| **Individual packaging dimensions - HxWxD (m):** | 0.013 x 0.185 x 0.285 |
| **Net weight per unit (kg):** | 0.018 |
| **Gross weight per unit (kg):** | 0.019 |

## Codes

| | |
|---|---|
| **GTIN-13 code:** | 8431044092041 |
| **Tariff code:** | 85366990 |
| **ETIM code 9.0:** | EC001320 |

## Downloads (links)

| | |
|---|---|
| **Product drawing STP (URL):** | https://ideelectric.com/docs/plans/stp/09204.stp |
| **Product drawing DXF (URL):** | https://ideelectric.com/docs/plans/dxf/09204.dxf |
| **Product drawing (PDF):** | https://ideelectric.com/docs/plans/pdf/09204.pdf |
| **Assembly instructions:** | https://assemblysteps.org/qr/ |