Ref: 09322

Serie IP44-IP67 Extra low voltage

IP44-IP67 Extra low-voltage

IP44 Extra low voltage wall socket 3P 42V (50/60HZ) 16A 12H



Features

Application:	Electrical connection
Suitable for outdoor installation:	No
Type of installation:	Wall-mounted
Rated current (A):	16
Voltage (V):	42
Frequency (Hz):	50/60
Poles:	3P
Clock position:	12
Color:	White

Technical data

Protection degree:	IP44
Resistance to impact:	IK08
Glow wire resistance (ºC):	960
Ball pressure test (°C):	125

Additional features

Flexible cable (mm²):	1-10
Rigid Cable (mm²):	1,5-10
Connection angle:	Angled
Phase Inverter:	No

Ref: 09322

Materials

Material of plastic parts:	Polyamide 6
Contact Material:	Copper-zinc alloy
Halogen-free materials:	Yes

Certificates and regulations

Directive:	2014/35/EU
Standards:	UNE-EN 60309-1; UNE-EN 60309-2; IEC 60884-1

Packaging

Supply:	Supplied in an individual box per packaging multiple
Individual Packaging Type:	Uncaged
UoM Packaging - Individual:	Unit
Minimum Selling Quantity:	10
Individual packaging dimensions - HxWxD (m):	0.22 x 0.185 x 0.285
Net weight per unit (kg):	0.24
Gross weight per unit (kg):	0.264

Codes

GTIN-13 code:	8431044093222
Tariff code:	85366990
ETIM code 9.0:	EC001321

Downloads (links)

Product drawing STP (URL):	https://ideelectric.com/docs/plans/stp/09322.stp
Product drawing DXF (URL):	https://ideelectric.com/docs/plans/dxf/09322.dxf
Product drawing (PDF):	https://ideelectric.com/docs/plans/pdf/09322.pdf
Assembly instructions:	https://assemblysteps.org/qr/