Ref: 40299

Serie Star Complet

IP54-IP44 Boxes with power sockets

IP54 1x9 mod. Box with power sockets



Features

Application:	Industrial (watertight and distribution enclosures),Construction
Suitable for outdoor installation:	Yes
Type of installation:	Surface
Material Quality:	ABS

Modular capacity

Box mounting:	CSN9PT
Capacity/Number of modules:	09
Number of rows:	1x9

Components:

Nº	Description	IP	Poles	Current (A)	Voltage (V)
1	Sloping flush-fit socket	44	3P+N+E	16	400
1	Sloping flush-fit socket	44	3P+N+E	32	400
2	Schuko-type sockets	54	2P+E	16	230

Technical data

Protection degree:	IP44
Resistance to impact:	IK08
Glow-wire resistance of enclosure (°C):	650
Ball pressure test on enclosure (°C):	70
Ball pressure in sockets (ºC):	125
Double insulation:	Class II

Dimensions

Piece dimensions - HxWxD (mm):	436 x 210 x 180
Top cable entry (mm):	4xM20-1xM40

Ref: 40299

Lower cable entry (mm):	2xM20-1xM40
Rear Oblong (mm):	2xOB25x25

Additional features

Emergency mushroom push button:	No
Door/window/lid type:	Transparent
Reversible door:	No
UV protection:	Yes
Lock type:	Snap closure
No. of locks:	1
Sealable:	Yes
Linkable:	Yes
Includes DIN Rail:	Yes

Materials

Halogen-free materials:	Yes
Body/Base Material:	ABS
Frame material:	ABS
Door/Lid/Window Material:	Polycarbonate (PC)
Lock material:	Acetal resin
Color:	Grey RAL 7035
Door color:	Smoked

Electrical properties

Maximum voltage (V):	1000 AC / 1500 DC

Ref: 40299

Certificates and regulations

Directive:	2014/35/EU
Standards:	UNE-EN 62208,UNE-EN 61439-1

Packaging

Supply:	Supplied fully assembled according to the specifications of each reference, protected with shrink wrap and packed in multiple cardboard packaging according to the number of units ordered With certificate of conformity, description, number of socket outlets and protection devices, and the corresponding single-line diagram
Individual Packaging Type:	Box
UoM Packaging - Individual:	Unit
Minimum Selling Quantity:	1
Individual packaging dimensions - HxWxD (m):	0.455 x 0.225 x 0.225
Net weight per unit (kg):	2.703
Gross weight per unit (kg):	2.974

Codes

GTIN-13 code:	8431044122175
Tariff code:	85371098
ETIM code 9.0:	EC000379

Downloads (links)

Assembly instructions:	https://assemblysteps.org/qr/