Ref: 42054

Serie Light Complet

IP44-IP54 Junction boxes with power sockets

Junction box EL231 with power sockets and plain sides



Features

Application:	Industrial (watertight and distribution enclosures),Construction
Suitable for outdoor installation:	No
Type of installation:	Surface
Material Quality:	Polystyrene (PS)

Modular capacity

Box mounting: EL231

Components:

Nº	Description	IP	Poles	Current (A)	Voltage (V)
2	Sloping flush-fit sockets	44	3P+N+E	16	400
2	Schuko-type sockets	54	2P+E	16	230

Technical data

Protection degree:	IP44
Resistance to impact:	IK07
Glow wire resistance (ºC):	650
Ball pressure test (°C):	70
Double insulation:	Class II

Dimensions

Piece dimensions - HxWxD (mm):	185 x 246 x 156

Additional features

Emergency mushroom push button:	No
Door/window/lid type:	Opaque
Door/lid/window fastening:	Screw-on

Ref: 42054

Reversible door:	No
UV protection:	No
Lock type:	With screws
Sealable:	Yes
Linkable:	No
Includes DIN Rail:	No

Materials

Halogen-free materials:	Yes
Color:	Grey RAL 7035

Electrical properties

Voltage (V):	230/400
Maximum voltage (V):	1000 AC / 1500 DC

Ref: 42054

Certificates and regulations

Directive:	2014/35/EU
Standards:	UNE-EN 60670-22

Packaging

Supply:	Supplied fully assembled according to the specifications of each reference, protected with shrink wrap and packed in multiple cardboard packaging according to the number of units ordered With certificate of conformity, description, number of socket outlets and protection devices, and the corresponding single-line diagram
Individual Packaging Type:	Wrap
UoM Packaging - Individual:	Unit
Minimum Selling Quantity:	1
Individual packaging dimensions - HxWxD (m):	0.386 x 0.388 x 0.586
Net weight per unit (kg):	1.289
Gross weight per unit (kg):	1.418

Codes

GTIN-13 code:	8431044420547
Tariff code:	85371098
ETIM code 9.0:	EC000379

Downloads (links)

Assembly instructions:	https://assemblysteps.org/qr/