Ref: BIG18016050POD/INX

Serie Argenta Plus BIG-INOX

IP65 Stainless steel compact cabinets

Floor-standing cabinet BIG INX IP55 1800x1600x500. Double door with plate



Features

Application:	Corrosive environments,Food industry
Suitable for outdoor installation:	No
Type of installation:	Floor-standing
Piece dimensions - HxWxD (mm):	1800 x 1600 x 500
Material Quality:	AISI 304 stainless steel

Technical data

Protection degree:	IP55
NEMA degree of protection:	1, 12
Resistance to impact:	IK10

Dimensions

Piece dimensions - HxWxD (mm):	1800 x 1600 x 500
Cable entry - WxD (mm):	500 x 200

Ref: BIG18016050POD/INX

Additional features

Door/window/lid type:	Double opaque
Reversible door:	Yes
Number of doors:	2
Body type:	Compact
Lock type:	Maneta de palanca + cilindro perfilado doble barra
Plate:	Yes
Plate Type:	Smooth
Adjustable Plate:	Yes
Perforated Plate:	No
No. of hinges:	4
No. of locks:	1x4P
Lock - Key Type:	5 mm double-bit Inactive door with internal 2-point locking. Profile cylinder not included

Materials

Lock material:	Cierre BIG-INOX
Plate material:	Galvanised steel
Gasket material:	Polyurethane
Finish:	Scotch 320 satin finish
Body thickness (mm):	1.5
Door thickness (mm):	2
Plate thickness (mm):	3
Cable entry cover thickness (mm):	2

Ref: BIG18016050POD/INX

Electrical properties

Maximum voltage (V): 1000 AC / 1500 DC

Rated current (A): Up to 3200 (depending on type of accessory)

Power dissipation:

Power dissipation P(W) as a function of temperature increase ΔT (°C)				
20	25	30	35	40
744.9	931.1	1117.4	1303.6	1489.8

Data calculated according to IEC TR 60890 using the method for verifying temperature rise in low-voltage switchgear and controlgear assemblies.

Certificates and regulations

Directive: 2014/35/EU

Standards: UNE-EN 62208,UNE-EN 61439-1

Packaging

Supply: Reinforced palletising with double channel kraft cardboard structural corner pieces
Front and rear protective sheet and highly transparent shrink wrap film Double QR code for information
The mounting plate is supplied assembled
5-mm double-bit lock zamak key

Individual Packaging Type: Pallet

UoM Packaging - Individual: Unit

Minimum Selling Quantity: 1

Individual packaging dimensions - HxWxD (m): 1.92 x 1.65 x 0.65

Net weight per unit (kg): 214.559

Gross weight per unit (kg): 236.014

Codes

GTIN-13 code: 8431044486949

Tariff code: 85381000

ETIM code 9.0: EC000261

Downloads (links)

Product drawing STP (URL): https://ideelectric.com/docs/plans/stp/BIG18016050PODINX.stp

Product drawing DXF (URL): https://ideelectric.com/docs/plans/dxf/BIG18016050PODINX.dxf

Ref: BIG18016050POD/INX

Product drawing (PDF):	https://ideelectric.com/docs/plans/pdf/BIG18016050PODINX.pdf
Product drawing EDZ (URL):	https://ideelectric.com/docs/plans/edz/IDE.BIG18016050PODINX.edz
Assembly instructions:	https://assemblysteps.org/qr/92871