Ref: BIG2008050PO/INX

Serie Argenta Plus BIG-INOX

IP65 Stainless steel compact cabinets

Floor-standing cabinet BIG INX IP65 2000x800x500. Opaque door with plate



Features

Application:	Corrosive environments,Food industry
Suitable for outdoor installation:	No
Type of installation:	Floor-standing
Piece dimensions - HxWxD (mm):	2000 x 800 x 500
Material Quality:	AISI 304 stainless steel

Technical data

Protection degree:	IP65
NEMA degree of protection:	1, 4, 4x, 12
Resistance to impact:	IK10

Dimensions

Piece dimensions - HxWxD (mm):	2000 x 800 x 500
Cable entry - WxD (mm):	500 x 300
Usable interior space - HxWxD (mm):	1910 x 710 x 457

Ref: BIG2008050PO/INX

Additional features

Door/window/lid type:	Single opaque
Reversible door:	Yes
Number of doors:	1
Body type:	Compact
Lock type:	Maneta de palanca + cilindro perfilado doble barra
Plate:	Yes
Plate Type:	Smooth
Adjustable Plate:	Yes
Perforated Plate:	No
No. of hinges:	4
No. of locks:	1x4P
Lock - Key Type:	5 mm double-bit Profile cylinder not included

Materials

Lock material:	Cierre BIG-INOX
Plate material:	Galvanised steel
Gasket material:	Polyurethane
Finish:	Scotch 320 satin finish
Body thickness (mm):	1.5
Door thickness (mm):	2
Plate thickness (mm):	3
Cable entry cover thickness (mm):	2

Ref: BIG2008050PO/INX

Electrical properties

Maximum voltage (V): 1000 AC / 1500 DC

Rated current (A): Up to 3200 (depending on type of accessory)

Power dissipation:

Power dissipation P(W) as a function of temperature increase ΔT (°C)				
20	25	30	35	40
506.0	632.5	759.0	885.5	1012.0

Data calculated according to IEC TR 60890 using the method for verifying temperature rise in low-voltage switchgear and controlgear assemblies.

Certificates and regulations

Directive: 2014/35/EU

Standards: UNE-EN 62208,UNE-EN 61439-1

Packaging

Supply: Reinforced palletising with double channel kraft cardboard structural corner pieces
Front and rear protective sheet and highly transparent shrink wrap film Double QR code for information
The mounting plate is supplied assembled
5-mm double-bit lock zamak key

Individual Packaging Type: Pallet

UoM Packaging - Individual: Unit

Minimum Selling Quantity: 1

Individual packaging dimensions - HxWxD (m): 2.12 x 0.85 x 0.55

Net weight per unit (kg): 133.5

Gross weight per unit (kg): 146.85

Codes

GTIN-13 code: 8431044216706

Tariff code: 85381000

ETIM code 9.0: EC000261

Downloads (links)

Product drawing STP (URL): https://ideelectric.com/docs/plans/stp/BIG2008050POINX.stp

Product drawing DXF (URL): https://ideelectric.com/docs/plans/dxf/BIG2008050POINX.dxf

Ref: BIG2008050PO/INX

Product drawing (PDF):	https://ideelectric.com/docs/plans/pdf/BIG2008050POINX.pdf
Product drawing EDZ (URL):	https://ideelectric.com/docs/plans/edz/IDE.BIG2008050POINX.edz
Assembly instructions:	https://assemblysteps.org/qr/92871