Ref: BT2

Serie Small Distribution Boxes

Small distribution boxes

IP20 Surface distribution box 2 modules sealable



Features

Application:	Domestic
Suitable for outdoor installation:	No
Type of installation:	Surface
Material Quality:	Polystyrene (PS)

Modular capacity

Capacity/Number of modules:	02
Number of rows:	1x2

Technical data

Protection degree:	IP20
Resistance to impact:	IK08
Glow wire resistance (ºC):	650
Ball pressure test (°C):	70
Double insulation:	Class II

Dimensions

Piece dimensions - HxWxD (mm):	130 x 50 x 64

Additional features

Door/window/lid type:	Without cover
Reversible door:	No
UV protection:	No
Sealable:	No

Ref: BT2

Linkable:	No
Neutral and earth bars:	No
Includes DIN Rail:	Yes
Plate:	No
Adjustable Plate:	No
Perforated Plate:	No

Materials

Halogen-free materials:	Yes
Body/Base Material:	Polystyrene (PS)
Frame material:	Polystyrene (PS)
Base color:	White RAL 9003
Frame color:	White RAL 9003

Ref: BT2

Electrical properties

Maximum voltage (V): 1000 AC / 1500 DC

Power dissipation:

Power dissipation P(W) as a function of temperature increase ΔT (°C)				
20	25	30	35	40
2.0	2.5	3.0	3.5	4.0

Data calculated according to IEC TR 60890 using the method for verifying temperature rise in low-voltage switchgear and controlgear assemblies.

Certificates and regulations

Directive: 2014/35/EU

Standards: UNE-EN 62208,UNE-EN 61439-1

Packaging

Supply: Supplied in individual packaging
When several items are sent together, they are bundled together with transparent film

Individual Packaging Type: Wrap

UoM Packaging - Individual: Unit

Minimum Selling Quantity: 36

Individual packaging dimensions - HxWxD (m): 0.004 x 0.31 x 0.42

Net weight per unit (kg): 0.072

Gross weight per unit (kg): 0.079

Codes

GTIN-13 code: 8431044240503

Tariff code: 85381000

ETIM code 9.0: EC000214

Downloads (links)

Assembly instructions: https://assemblysteps.org/qr/