Ref: CT1515/PH

Serie Domos-Kjunction

Junction boxes. Flush-fit for hollow walls

Junction box flush-fit hollow walls 134x134x61



Features

Application:	Domestic
Suitable for outdoor installation:	No
Type of installation:	Recessed hollow walls
Material Quality:	Polystyrene (PS)

Technical data

Glow wire resistance (ºC):	850

Dimensions

Piece dimensions - HxWxD (mm):	153 x 153 x 64
Box flush-mounting cut-out dimensions - H×W×D (mm):	134 x 134 x 61

Additional features

Door/window/lid type:	Screw-fastened opaque
Door/lid/window fastening:	Screw-on
Reversible door:	No
UV protection:	No
Number of doors:	1
Lock type:	With screws
Sealable:	No
Linkable:	No
Neutral and earth bars:	No
Includes DIN Rail:	No

Ref: CT1515/PH

Equipped with:	Other
Cable entry type:	Pre-punched
Plate:	No
Adjustable Plate:	No
Perforated Plate:	No
Form:	Square

Materials

Halogen-free materials:	Yes
Body/Base Material:	ABS
Door/Lid/Window Material:	Polystyrene (PS)
Color:	White RAL 9003
Base color:	White RAL 9003

Ref: CT1515/PH

Electrical properties

Maximum voltage (V): 1000 AC / 1500 DC

Power dissipation:

Power dissipation P(W) as a function of temperature increase ΔT (°C)				
20	25	30	35	40
2.7	3.4	4.1	4.8	5.5

Data calculated according to IEC TR 60890 using the method for verifying temperature rise in low-voltage switchgear and controlgear assemblies.

Packaging

Supply: Supplied with: Cover and bag of screws for assembly in hollow walls
Supplied in an individual box per packaging multiple

Individual Packaging Type: Wrap

UoM Packaging - Individual: Unit

Minimum Selling Quantity: 56

Individual packaging dimensions - HxWxD (m): 0.153 x 0.153 x 0.064

Net weight per unit (kg): 0.182

Gross weight per unit (kg): 0.2

Codes

GTIN-13 code: 8431044564265

Tariff code: 85381000

ETIM code 9.0: EC002601

Downloads (links)

Product drawing (PDF): https://ideelectric.com/docs/plans/pdf/CT1515PH.pdf

Assembly instructions: https://assemblysteps.org/qr/91452