Ref: CT4040

Serie Domos junction

Junction boxes. Flush-fit for brick walls

Junction box flush-fit brick walls 406x406x122



Features

Application:	Domestic
Suitable for outdoor installation:	No
Type of installation:	Recessed conventional walls
Material Quality:	Polystyrene (PS)

Technical data

Protection degree:	IP33
Resistance to impact:	IK07
Glow wire resistance (ºC):	650
Double insulation:	Class II

Dimensions

Piece dimensions - HxWxD (mm):	407 x 407 x 125
Box flush-mounting cut-out dimensions - H×W×D (mm):	406 x 406 x 122

Additional features

Door/window/lid type:	Screw-fastened opaque
Door/lid/window fastening:	Screw-on
Reversible door:	No
UV protection:	No
Number of doors:	1
Lock type:	With screws
Sealable:	No

Ref: CT4040

Linkable:	No
Neutral and earth bars:	No
Includes DIN Rail:	No
Plate:	No
Adjustable Plate:	No
Perforated Plate:	No

Materials

Halogen-free materials:	Yes
Body/Base Material:	Polystyrene (PS)
Door/Lid/Window Material:	Polystyrene (PS)
Color:	White RAL 9003
Base color:	Black

Ref: CT4040

Electrical properties

Maximum voltage (V): 1000 AC / 1500 DC

Power dissipation:

Power dissipation P(W) as a function of temperature increase ΔT (°C)				
20	25	30	35	40
21.9	27.4	32.9	38.3	43.8

Data calculated according to IEC TR 60890 using the method for verifying temperature rise in low-voltage switchgear and controlgear assemblies.

Certificates and regulations

Directive: 2014/35/EU

Standards: UNE-EN 62208; UNE-EN 60670-1

Packaging

Supply: The boxes are supplied individually, shrink-wrapped and in multiple cardboard packaging, according to minimum packaging units

Individual Packaging Type: Wrap

UoM Packaging - Individual: Unit

Minimum Selling Quantity: 2

Individual packaging dimensions - HxWxD (m): 0.407 x 0.407 x 0.125

Net weight per unit (kg): 1.606

Gross weight per unit (kg): 1.766

Codes

GTIN-13 code: 8431044270203

Tariff code: 85381000

ETIM code 9.0: EC002601

Downloads (links)

Product drawing STP (URL): https://ideelectric.com/docs/plans/stp/CT4040.stp

Product drawing DXF (URL): https://ideelectric.com/docs/plans/dxf/CT4040.dxf

Product drawing (PDF): https://ideelectric.com/docs/plans/pdf/CT4040.pdf

Assembly instructions: https://assemblysteps.org/qr/91204