Ref: D88

Serie Domos wiring

Wiring boxes. Flush-fit for brick walls

Mechanism box flush-fit brick walls 71x71x43



Features

Application:	Domestic
Suitable for outdoor installation:	No
Type of installation:	Recessed conventional walls
Material Quality:	Polystyrene (PS)

Technical data

Glow wire resistance (ºC):	650
Ball pressure test (°C):	70

Dimensions

Piece dimensions - HxWxD (mm):	71 x 71 x 43
Box flush-mounting cut-out dimensions - H×W×D (mm):	71 x 71 x 43

Additional features

Door/window/lid type:	Without cover
Reversible door:	No
UV protection:	No
Lock type:	-
Sealable:	No
Linkable:	No
Neutral and earth bars:	No
Includes DIN Rail:	No
Plate:	No

Ref: D88

Adjustable Plate:	No
Perforated Plate:	No

Materials

Halogen-free materials:	Yes
Color:	Black

Ref: D88

Electrical properties

Maximum voltage (V): 1000 AC / 1500 DC

Power dissipation:

Power dissipation P(W) as a function of temperature increase ΔT (°C)				
20	25	30	35	40
0.9	1.1	1.3	1.5	1.7

Data calculated according to IEC TR 60890 using the method for verifying temperature rise in low-voltage switchgear and controlgear assemblies.

Certificates and regulations

Directive: 2014/35/EU

Standards: UNE-EN 60670-1-22

Packaging

Supply: The boxes are supplied individually, shrink-wrapped and in multiple cardboard packaging, according to minimum packaging units
The D88 boxes are supplied on pallets Minimum amount of 7680 pieces per order
Their storage system permits 20% space saving

Individual Packaging Type: Wrap

UoM Packaging - Individual: Unit

Minimum Selling Quantity: 640

Individual packaging dimensions - HxWxD (m): 0.071 x 0.071 x 0.043

Net weight per unit (kg): 0.026

Gross weight per unit (kg): 0.029

Codes

GTIN-13 code: 8431044458502

Tariff code: 85381000

ETIM code 9.0: EC002601

Downloads (links)

Assembly instructions: https://assemblysteps.org/qr/