Ref: DFF42PO/PH

Serie Diamant

IP40 Flush-fit plastic boxes

IP40 distribution box flush-fit hollow wall 3x14 (42) modules



Features

Application:	Domestic
Suitable for outdoor installation:	No
Type of installation:	Recessed hollow walls
Material Quality:	Polystyrene (PS)

Modular capacity

Capacity/Number of modules:	042
Number of rows:	3x14

Technical data

Protection degree:	IP40
Resistance to impact:	IK08
Glow wire resistance (ºC):	850
Ball pressure test (°C):	70
Double insulation:	Class II

Dimensions

Piece dimensions - HxWxD (mm):	532 x 334 x 105
Box flush-mounting cut-out dimensions - H×W×D (mm):	500 x 305 x 72

Additional features

Door/window/lid type:	Opaque
Door/lid/window fastening:	Snap-fit
Reversible door:	Yes

Ref: DFF42PO/PH

UV protection:	No
Number of doors:	1
Lock type:	Snap-on door
Sealable:	No
Linkable:	Yes
Neutral and earth bars:	No
Includes DIN Rail:	Yes
Plate:	No
Adjustable Plate:	No
Perforated Plate:	No

Materials

Halogen-free materials:	Yes
Body/Base Material:	ABS
Frame material:	Polystyrene (PS)
Door/Lid/Window Material:	Polystyrene (PS)
Base color:	Grey RAL 7035
Frame color:	White RAL 9003
Door color:	White RAL 9003

Ref: DFF42PO/PH

Electrical properties

Maximum voltage (V): 1000 AC / 1500 DC

Power dissipation:

Power dissipation P(W) as a function of temperature increase ΔT (°C)				
20	25	30	35	40
21.3	26.6	31.9	37.2	42.5

Data calculated according to IEC TR 60890 using the method for verifying temperature rise in low-voltage switchgear and controlgear assemblies.

Certificates and regulations

Directive: 2014/35/EU

Standards: UNE-EN 62208,UNE-EN 61439-1

Packaging

Supply: Supplied in individual packaging
When several items are sent together, they are bundled together with transparent film
Supplied with all the elements assembled, except for the elements supplied in the accessory bag

Accessories bag:
4x12 bolts
4x13 bolts
Caps for 4x13 bolts
Hollow wall fasteners
Linking pieces (for boxes with 72-84-108 modules)
Cover for white modules (6 modules)
Module identification strip

Individual Packaging Type: Wrap

UoM Packaging - Individual: Unit

Minimum Selling Quantity: 6

Individual packaging dimensions - HxWxD (m): 0.54 x 0.337 x 0.118

Net weight per unit (kg): 2.597

Gross weight per unit (kg): 2.857

Codes

GTIN-13 code: 8431044165288

Tariff code: 85381000

ETIM code 9.0: EC000214

Ref: DFF42PO/PH

Downloads (links)

Product drawing DXF (URL):	https://ideelectric.com/docs/plans/dxf/DFF42POPH.dxf
Product drawing (PDF):	https://ideelectric.com/docs/plans/pdf/DFF42POPH.pdf
Assembly instructions:	https://assemblysteps.org/qr/92955