Ref: ENLBP2008060PT/SP

Serie Argenta Plus Rack 19"

19"-Rack cabinets

ENL cabinet with swing frame 2000x800x600. Transparent door without plate



Features

Application:	Major engineering projects
Suitable for outdoor installation:	No
Type of installation:	Floor-standing
Piece dimensions - HxWxD (mm):	2000 x 800 x 600
Material Quality:	Cold-rolled steel

Technical data

Protection degree:	IP55
NEMA degree of protection:	1, 12
Resistance to impact:	IK09

Dimensions

Piece dimensions - HxWxD (mm):	2000 x 800 x 600
Cable entry - WxD (mm):	570 x 510
Glass door visible area - HxW (mm):	1786 x 420

Ref: ENLBP2008060PT/SP

Additional features

Door/window/lid type:	Single transparent
Reversible door:	Yes
Number of doors:	1
Body type:	Linkable
Lock type:	Lever handle + 5-mm double-bit insert
Plate:	No
Adjustable Plate:	No
Perforated Plate:	No
No. of hinges:	4
No. of locks:	1x4P
Lock - Key Type:	5 mm double-bit Zamak key included

Materials

Door/Lid/Window Material:	Tempered glass
Lock material:	Zamak insert and handle in blue polyamide RAL 5013 and anthracite grey RAL 7016
Mounting frame material:	Zinc-plated steel
Gasket material:	Polyurethane
Color:	Grey RAL 7035
Finish:	Primed and painted with embossed polyester paint
Door thickness (mm):	4
Side panel thickness (mm):	1.5
Cable entry cover thickness (mm):	1.2

Ref: ENLBP2008060PT/SP

Maximum loads

Maximum total load (kg): 100

Electrical properties

Maximum voltage (V): 1000 AC / 1500 DC

Rated current (A): Up to 6200 (depending on type of accessory)

Power dissipation:

Power dissipation P(W) as a function of temperature increase ΔT (°C)				
20	25	30	35	40
557.9	697.4	836.9	976.4	1115.8

Data calculated according to IEC TR 60890 using the method for verifying temperature rise in low-voltage switchgear and controlgear assemblies.

Certificates and regulations

Directive: 2014/35/EU

Standards: UNE-EN 62208,UNE-EN 61439-1

Packaging

Supply: Supplied on a pallet, protected with honeycomb cardboard corner protectors and shrink wrap

Individual Packaging Type: Pallet

UoM Packaging - Individual: Unit

Minimum Selling Quantity: 1

Individual packaging dimensions - HxWxD (m): 2.175 x 0.85 x 0.75

Net weight per unit (kg): 151.072

Gross weight per unit (kg): 166.179

Codes

GTIN-13 code: 8431044059501

Tariff code: 85381000

ETIM code 9.0: EC000261

Downloads (links)

Product drawing (PDF): https://ideelectric.com/docs/plans/pdf/ENLBP2008060PTSP.pdf

Ref: ENLBP2008060PT/SP

Assembly instructions:	https://assemblysteps.org/qr/91085
Videos:	ARGENTA PLUS PO ENL (ESP-ING)