**Ref: ENLBP2208060PT/SP**

# Serie Argenta Plus Rack 19"

## 19"-Rack cabinets

ENL cabinet with swing frame 2200x800x600. Transparent door without plate



## Features

| | |
|---|---|
| **Application:** | Major engineering projects |
| **Suitable for outdoor installation:** | No |
| **Type of installation:** | Floor-standing |
| **Piece dimensions - HxWxD (mm):** | 2200 x 800 x 600 |
| **Material Quality:** | Cold-rolled steel |

## Technical data

| | |
|---|---|
| **Protection degree:** | IP55 |
| **NEMA degree of protection:** | 1, 12 |
| **Resistance to impact:** | IK09 |

## Dimensions

| | |
|---|---|
| **Piece dimensions - HxWxD (mm):** | 2200 x 800 x 600 |
| **Cable entry - WxD (mm):** | 570 x 510 |
| **Glass door visible area - HxW (mm):** | 1986 x 420 |

## Ref: ENLBP2208060PT/SP

### Additional features

| | |
|---|---|
| **Door/window/lid type:** | Single transparent |
| **Reversible door:** | Yes |
| **Number of doors:** | 1 |
| **Body type:** | Linkable |
| **Lock type:** | Lever handle + 5-mm double-bit insert |
| **Plate:** | No |
| **Adjustable Plate:** | No |
| **Perforated Plate:** | No |
| **No. of hinges:** | 4 |
| **No. of locks:** | 1x4P |
| **Lock - Key Type:** | 5 mm double-bit Zamak key included |

### Materials

| | |
|---|---|
| **Door/Lid/Window Material:** | Tempered glass |
| **Lock material:** | Zamak insert and handle in blue polyamide RAL 5013 and anthracite grey RAL 7016 |
| **Mounting frame material:** | Zinc-plated steel |
| **Gasket material:** | Polyurethane |
| **Color:** | Grey RAL 7035 |
| **Finish:** | Primed and painted with embossed polyester paint |
| **Door thickness (mm):** | 4 |
| **Side panel thickness (mm):** | 1.5 |
| **Cable entry cover thickness (mm):** | 1.2 |

## Ref: ENLBP2208060PT/SP

### Maximum loads

**Maximum total load (kg):** 100

### Electrical properties

**Maximum voltage (V):** 1000 AC / 1500 DC

**Rated current (A):** Up to 6200 (depending on type of accessory)

**Power dissipation:**

| Power dissipation P(W) as a function of temperature increase ΔT (°C) | | | | |
|---|---|---|---|---|
| 20 | 25 | 30 | 35 | 40 |
| 606.3 | 757.9 | 909.5 | 1061.1 | 1212.6 |

Data calculated according to IEC TR 60890 using the method for verifying temperature rise in low-voltage switchgear and controlgear assemblies.

### Certificates and regulations

**Directive:** 2014/35/EU

**Standards:** UNE-EN 62208,UNE-EN 61439-1

### Packaging

**Supply:** Supplied on a pallet, protected with honeycomb cardboard corner protectors and shrink wrap

**Individual Packaging Type:** Pallet

**UoM Packaging - Individual:** Unit

**Minimum Selling Quantity:** 1

**Individual packaging dimensions - HxWxD (m):** 2.32 x 0.85 x 0.75

**Net weight per unit (kg):** 161.353

**Gross weight per unit (kg):** 177.488

### Codes

**GTIN-13 code:** 8431044059525

**Tariff code:** 85381000

**ETIM code 9.0:** EC000261

### Downloads (links)

**Product drawing (PDF):** https://ideelectric.com/docs/plans/pdf/ENLBP2208060PTSP.pdf

## Ref: ENLBP2208060PT/SP

| | |
|---|---|
| **Assembly instructions:** | https://assemblysteps.org/qr/91085 |
| **Videos:** | ARGENTA PLUS PO ENL (ESP-ING) |