Ref: ENLPC1656060

Serie PC Control Cabinet

IP55 PC control cabinet

IP55 PC control cabinet 1650x600x600. Transparent door



Features

Application:	Automation and control
Suitable for outdoor installation:	No
Type of installation:	Floor-standing
Piece dimensions - HxWxD (mm):	1650 x 600 x 600
Material Quality:	Cold-rolled steel

Technical data

Protection degree:	IP55
Resistance to impact:	IK09

Dimensions

Piece dimensions - HxWxD (mm):	1650 x 600 x 600
Cable entry - WxD (mm):	370 x 510

Ref: ENLPC1656060

Additional features

Door/window/lid type:	Single transparent
Reversible door:	Yes
Number of doors:	1
Body type:	Linkable
Lock type:	1.5x3 slot
Plate:	No
Adjustable Plate:	No
Perforated Plate:	No
No. of hinges:	4
No. of locks:	4x1P

Materials

Gasket material:	Polyurethane
Color:	Grey RAL 7035
Finish:	Primed and painted with embossed polyester paint
Body thickness (mm):	1.5
Door thickness (mm):	4
Cable entry cover thickness (mm):	1.2

Ref: ENLPC1656060

Electrical properties

Maximum voltage (V): 1000 AC / 1500 DC

Rated current (A): Up to 6200 (depending on type of accessory)

Power dissipation:

Power dissipation P(W) as a function of temperature increase ΔT (°C)				
20	25	30	35	40
403.9	504.9	605.9	706.9	807.8

Certificates and regulations

Directive: 2014/35/EU

Standards: UNE-EN 62208,UNE-EN 61439-1

Packaging

Supply: Supplied on a pallet, protected with honeycomb cardboard corner protectors and shrink wrap Includes two lifting eye bolts to facilitate transport

Individual Packaging Type: Pallet

UoM Packaging - Individual: Unit

Minimum Selling Quantity: 1

Individual packaging dimensions - HxWxD (m): 1.9 x 0.7 x 0.7

Net weight per unit (kg): 111.009

Gross weight per unit (kg): 122.11

Codes

GTIN-13 code: 8431044088051

Tariff code: 85381000

ETIM code 9.0: EC002499

Downloads (links)

Product drawing (PDF): https://ideelectric.com/docs/plans/pdf/ENLPC1656060.pdf

Assembly instructions: https://assemblysteps.org/qr/92871