**Ref: ENLPC1656060/PMO**

# Serie PC Control Cabinet

## IP55 PC control cabinet

IP55 PC control cabinet 1650x600x600. Opaque door



## Features

| | |
|---|---|
| **Application:** | Automation and control |
| **Suitable for outdoor installation:** | No |
| **Type of installation:** | Floor-standing |
| **Piece dimensions - HxWxD (mm):** | 1650 x 600 x 600 |
| **Material Quality:** | Cold-rolled steel |

## Technical data

| | |
|---|---|
| **Protection degree:** | IP55 |
| **Resistance to impact:** | IK10 |

## Dimensions

| | |
|---|---|
| **Piece dimensions - HxWxD (mm):** | 1650 x 600 x 600 |
| **Cable entry - WxD (mm):** | 370 x 510 |

## Ref: ENLPC1656060/PMO

### Additional features

| | |
|---|---|
| **Door/window/lid type:** | Single opaque |
| **Reversible door:** | Yes |
| **Number of doors:** | 1 |
| **Body type:** | Linkable |
| **Lock type:** | 1.5x3 slot |
| **Plate:** | No |
| **Adjustable Plate:** | No |
| **Perforated Plate:** | No |
| **No. of hinges:** | 4 |
| **No. of locks:** | 4x1P |

### Materials

| | |
|---|---|
| **Gasket material:** | Polyurethane |
| **Color:** | Grey RAL 7035 |
| **Finish:** | Primed and painted with embossed polyester paint |
| **Body thickness (mm):** | 1.5 |
| **Door thickness (mm):** | 2 |
| **Cable entry cover thickness (mm):** | 1.2 |

# Ref: ENLPC1656060/PMO

## Electrical properties

**Maximum voltage (V):** 1000 AC / 1500 DC

**Rated current (A):** Up to 6200 (depending on type of accessory)

**Power dissipation:**

| Power dissipation P(W) as a function of temperature increase ΔT (°C) | | | | |
|---|---|---|---|---|
| 20 | 25 | 30 | 35 | 40 |
| 403.9 | 504.9 | 605.9 | 706.9 | 807.8 |

## Certificates and regulations

**Directive:** 2014/35/EU

**Standards:** UNE-EN 62208,UNE-EN 61439-1

## Packaging

**Supply:** Supplied on a pallet, protected with honeycomb cardboard corner protectors and shrink wrap Includes two lifting eye bolts to facilitate transport

**Individual Packaging Type:** Pallet

**UoM Packaging - Individual:** Unit

**Minimum Selling Quantity:** 1

**Individual packaging dimensions - HxWxD (m):** 1.9 x 0.7 x 0.7

**Net weight per unit (kg):** 108.882

**Gross weight per unit (kg):** 119.77

## Codes

**GTIN-13 code:** 8431044135489

**Tariff code:** 85381000

**ETIM code 9.0:** EC002499

## Downloads (links)

**Product drawing (PDF):** https://ideelectric.com/docs/plans/pdf/ENLPC1656060PMO.pdf

**Assembly instructions:** https://assemblysteps.org/qr/92871