Ref: ENLPC1656080

Serie PC Control Cabinet

IP55 PC control cabinet

IP55 PC control cabinet 1650x600x800. Transparent door



Features

Application:	Automation and control
Suitable for outdoor installation:	No
Type of installation:	Floor-standing
Piece dimensions - HxWxD (mm):	1650 x 600 x 800
Material Quality:	Cold-rolled steel

Technical data

Protection degree:	IP55
Resistance to impact:	IK09

Dimensions

Piece dimensions - HxWxD (mm):	1650 x 600 x 800
Cable entry - WxD (mm):	370 x 710

Ref: ENLPC1656080

Additional features

Door/window/lid type:	Single transparent
Reversible door:	Yes
Number of doors:	1
Body type:	Linkable
Lock type:	1.5x3 slot
Plate:	No
Adjustable Plate:	No
Perforated Plate:	No
No. of hinges:	4
No. of locks:	4x1P

Materials

Gasket material:	Polyurethane
Color:	Grey RAL 7035
Finish:	Primed and painted with embossed polyester paint
Body thickness (mm):	1.5
Door thickness (mm):	4
Cable entry cover thickness (mm):	1.2

Ref: ENLPC1656080

Electrical properties

Maximum voltage (V):	1000 AC / 1500 DC
Rated current (A):	Up to 6200 (depending on type of accessory)

Certificates and regulations

Directive:	2014/35/EU
Standards:	UNE-EN 62208,UNE-EN 61439-1

Packaging

Supply:	Supplied on a pallet, protected with honeycomb cardboard corner protectors and shrink wrap Includes two lifting eye bolts to facilitate transport
Individual Packaging Type:	Pallet
UoM Packaging - Individual:	Unit
Minimum Selling Quantity:	1
Individual packaging dimensions - HxWxD (m):	1.825 x 0.7 x 0.95
Net weight per unit (kg):	123.6
Gross weight per unit (kg):	135.96

Codes

GTIN-13 code:	8431044088075
Tariff code:	85381000
ETIM code 9.0:	EC002499

Downloads (links)

Product drawing (PDF):	https://ideelectric.com/docs/plans/pdf/ENLPC1656080.pdf
Assembly instructions:	https://assemblysteps.org/qr/92871