**Ref: GN403015/SP**

# Serie Argenta

## IP66 Rolled Steel cabinets

IP66 rolled steel wall cabinet 400x300x150. Opaque door without plate



## Features

| | |
|---|---|
| **Application:** | Automation and control |
| **Suitable for outdoor installation:** | No |
| **Type of installation:** | Wall-mounted |
| **Piece dimensions - HxWxD (mm):** | 400 x 300 x 150 |
| **Material Quality:** | Cold-rolled steel |

## Technical data

| | |
|---|---|
| **Protection degree:** | IP66 |
| **NEMA degree of protection:** | 1, 4, 12 |
| **Resistance to impact:** | IK08 |

## Dimensions

| | |
|---|---|
| **Piece dimensions - HxWxD (mm):** | 400 x 300 x 150 |
| **Cable entry - WxD (mm):** | 65 x 185 |
| **Wall Mounting - HxW (mm):** | 360 x 260 |
| **Usable interior space - HxWxD (mm):** | 350 x 250 x 129 |

## Ref: GN403015/SP

### Additional features

| | |
|---|---|
| **Door/window/lid type:** | Single opaque |
| **Reversible door:** | Yes |
| **Number of doors:** | 1 |
| **Body type:** | Compact |
| **Lock type:** | 5-mm double-bit |
| **Plate:** | No |
| **Adjustable Plate:** | No |
| **Perforated Plate:** | No |
| **No. of hinges:** | 2 |
| **No. of locks:** | 1x1P |
| **Lock - Key Type:** | 5 mm double-bit Polyamide key included |
| **No. of door profiles:** | 2 |

### Materials

| | |
|---|---|
| **Lock material:** | Insert, cam and housing in grey polyamide RAL 7037 |
| **Gasket material:** | Polyurethane |
| **Color:** | Grey RAL 7035 |
| **Finish:** | Primed and painted with embossed polyester paint |
| **Body thickness (mm):** | 1.2 |
| **Door thickness (mm):** | 1.2 |
| **Cable entry cover thickness (mm):** | 2 |

## Ref: GN403015/SP

### Maximum loads

| | |
|---|---|
| **Maximum total load (kg):** | 175 |
| **Maximum door load (kg):** | 25 |

### Electrical properties

| | |
|---|---|
| **Maximum voltage (V):** | 1000 AC / 1500 DC |

**Power dissipation:**

| Power dissipation P(W) as a function of temperature increase ΔT (°C) | | | | |
|---|---|---|---|---|
| 20 | 25 | 30 | 35 | 40 |
| 37.3 | 46.6 | 55.9 | 65.3 | 74.6 |

Data calculated according to IEC TR 60890 using the method for verifying temperature rise in low-voltage switchgear and controlgear assemblies.

### Certificates and regulations

| | |
|---|---|
| **Directive:** | Low voltage directive,RoHS Directive |
| **Regulation:** | UK Electrical Equipment Safety Regulations |
| **Standards:** | EN 62208 |

### Packaging

**Supply:**

Supplied in individual packaging containing cabinet, plate and accessory bag
**Mounting plate:**
For cabinets with a height ≤ 700 mm and width < 800 mm are supplied unassembled in the packaging
For cabinets with a height ≤ 700 mm and width ≥ 800 mm are supplied assembled
For cabinets with a height > 700 mm are supplied assembled
**Accessory bag:**
4 watertight caps (if the wall-mounting cut-out holes are not used)
Nut and washer kit for securing the earth wire
Plate height adjusters, nuts, washers and drainage plug
5 mm double-bit key
Cable-entry cover and fixing screws

| | |
|---|---|
| **Individual Packaging Type:** | Box |
| **UoM Packaging - Individual:** | Unit |
| **Minimum Selling Quantity:** | 1 |
| **Individual packaging dimensions - HxWxD (m):** | 0.42 x 0.315 x 0.17 |
| **Net weight per unit (kg):** | 5.778 |
| **Gross weight per unit (kg):** | 6.356 |

### Codes

## Ref: GN403015/SP

| | |
|---|---|
| **GTIN-13 code:** | 8431044118253 |
| **Tariff code:** | 85381000 |
| **ETIM code 9.0:** | EC000261 |

## Downloads (links)

| | |
|---|---|
| **Product drawing STP (URL):** | https://ideelectric.com/docs/plans/stp/GN403015SP.stp |
| **Product drawing DXF (URL):** | https://ideelectric.com/docs/plans/dxf/GN403015SP.dxf |
| **Product drawing (PDF):** | https://ideelectric.com/docs/plans/pdf/GN403015SP.pdf |
| **Product drawing EDZ (URL):** | https://ideelectric.com/docs/plans/edz/IDE.GN403015SP.edz |
| **Assembly instructions:** | https://assemblysteps.org/qr/92890 |