Ref: GN808040/SP

Serie Argenta

IP66 Rolled Steel cabinets

IP66 rolled steel wall cabinet 800x800x400. Opaque door without plate



Features

Application:	Automation and control
Suitable for outdoor installation:	No
Type of installation:	Wall-mounted
Piece dimensions - HxWxD (mm):	800 x 800 x 400
Material Quality:	Cold-rolled steel

Technical data

Protection degree:	IP66
NEMA degree of protection:	1, 4, 12
Resistance to impact:	IK10

Dimensions

Piece dimensions - HxWxD (mm):	800 x 800 x 400
Cable entry - WxD (mm):	125 x 685
Wall Mounting - HxW (mm):	760 x 760
Usable interior space - HxWxD (mm):	750 x 750 x 379

Ref: GN808040/SP

Additional features

Door/window/lid type:	Single opaque
Reversible door:	Yes
Number of doors:	1
Body type:	Compact
Lock type:	5-mm double-bit
Plate:	No
Adjustable Plate:	No
Perforated Plate:	No
No. of hinges:	3
No. of locks:	2x1P
Lock - Key Type:	5 mm double-bit Polyamide key included
No. of door profiles:	2

Materials

Lock material:	Insert, cam and housing in grey polyamide RAL 7037
Gasket material:	Polyurethane
Color:	Grey RAL 7035
Finish:	Primed and painted with embossed polyester paint
Body thickness (mm):	1.5
Door thickness (mm):	1.5
Cable entry cover thickness (mm):	2

Ref: GN808040/SP

Maximum loads

Maximum total load (kg):	325
Maximum door load (kg):	25

Electrical properties

Maximum voltage (V):	1000 AC / 1500 DC

Power dissipation:

Power dissipation P(W) as a function of temperature increase ΔT (°C)				
20	25	30	35	40
211.2	264.0	316.8	369.6	422.4

Data calculated according to IEC TR 60890 using the method for verifying temperature rise in low-voltage switchgear and controlgear assemblies.

Certificates and regulations

Directive:	Low voltage directive,RoHS Directive
Regulation:	UK Electrical Equipment Safety Regulations
Standards:	EN 62208

Packaging

Supply:

Supplied in individual packaging containing cabinet, plate and accessory bag
Mounting plate:
For cabinets with a height ≤ 700 mm and width < 800 mm are supplied unassembled in the packaging
For cabinets with a height ≤ 700 mm and width ≥ 800 mm are supplied assembled
For cabinets with a height > 700 mm are supplied assembled
Accessory bag:
4 watertight caps (if the wall-mounting cut-out holes are not used)
Nut and washer kit for securing the earth wire
Plate height adjusters, nuts, washers and drainage plug
5 mm double-bit key
Cable-entry cover and fixing screws

Individual Packaging Type:	Box
UoM Packaging - Individual:	Unit
Minimum Selling Quantity:	1
Individual packaging dimensions - HxWxD (m):	0.82 x 0.815 x 0.42
Net weight per unit (kg):	36.876
Gross weight per unit (kg):	40.564

Codes

Ref: GN808040/SP

GTIN-13 code:	8431044118543
Tariff code:	85381000
ETIM code 9.0:	EC000261

Downloads (links)

Product drawing STP (URL):	https://ideelectric.com/docs/plans/stp/GN808040SP.stp
Product drawing DXF (URL):	https://ideelectric.com/docs/plans/dxf/GN808040SP.dxf
Product drawing (PDF):	https://ideelectric.com/docs/plans/pdf/GN808040SP.pdf
Product drawing EDZ (URL):	https://ideelectric.com/docs/plans/edz/IDE.GN808040SP.edz
Assembly instructions:	https://assemblysteps.org/qr/92890