Ref: GNG403020

Serie Argenta Galvanised Steel

IP66 Galvanised steel cabinets

IP66 galvanised steel wall cabinet 400x300x200. Opaque door with plate



Features

Application:	Automation and control,Corrosive environments
Suitable for outdoor installation:	No
Type of installation:	Wall-mounted
Piece dimensions - HxWxD (mm):	400 x 300 x 200
Material Quality:	Galvanised steel

Technical data

Protection degree:	IP66
NEMA degree of protection:	1, 4, 12
Resistance to impact:	IK08

Dimensions

Piece dimensions - HxWxD (mm):	400 x 300 x 200
Plate dimensions - HxW (mm):	370 x 250
Cable entry - WxD (mm):	125 x 125
Wall Mounting - HxW (mm):	360 x 260
Usable interior space - HxWxD (mm):	350 x 250 x 179

Ref: GNG403020

Additional features

Door/window/lid type:	Single opaque
Reversible door:	Yes
Number of doors:	1
Body type:	Compact
Lock type:	5-mm double-bit
Plate:	Yes
Plate Type:	Smooth
Adjustable Plate:	No
Perforated Plate:	No
No. of hinges:	2
No. of locks:	1x1P
Lock - Key Type:	5 mm double-bit Polyamide key included
No. of door profiles:	2

Materials

Lock material:	Insert, cam and housing in grey polyamide RAL 7037
Plate material:	Galvanised steel
Gasket material:	Polyurethane
Color:	Grey RAL 7035
Finish:	Primed and painted with embossed polyester paint
Body thickness (mm):	1.2
Door thickness (mm):	1.2
Plate thickness (mm):	2
Cable entry cover thickness (mm):	2

Ref: GNG403020

Maximum loads

Maximum total load (kg):	175
Maximum door load (kg):	25
Maximum plate load (kg):	150

Electrical properties

Maximum voltage (V):	1000 AC / 1500 DC

Power dissipation:

Power dissipation P(W) as a function of temperature increase ΔT (°C)				
20	25	30	35	40
43.5	54.4	65.3	76.2	87.1

Data calculated according to IEC TR 60890 using the method for verifying temperature rise in low-voltage switchgear and controlgear assemblies.

Certificates and regulations

Directive:	2014/35/EU
Standards:	UNE-EN 62208,UNE-EN 61439-1

Packaging

Supply:

Supplied in individual packaging containing cabinet, plate andaccessory bag
Mounting plate:
For cabinets with a height ≤700 mm and width <800 mm are supplied unassembled in the packaging
For cabinets with a height ≤700 mm and width ≥800 mm are supplied assembled
For cabinets with a height >700 mm are supplied assembled
Accessory bag:
4 watertight caps (if the wall-mounting cut-out holes are not used)
Nut and washer kit for securing the earth wire
Plate height adjusters, nuts, washers and drainage caps
5 mm double-bit key
Cable-entry cover and fixing screws

Individual Packaging Type:	Box
UoM Packaging - Individual:	Unit
Minimum Selling Quantity:	1
Individual packaging dimensions - HxWxD (m):	0.42 x 0.315 x 0.22
Net weight per unit (kg):	8.166
Gross weight per unit (kg):	8.983

Codes

Ref: GNG403020

GTIN-13 code:	8431044426815
Tariff code:	85381000
ETIM code 9.0:	EC000261

Downloads (links)

Product drawing STP (URL):	https://ideelectric.com/docs/plans/stp/GNG403020.stp
Product drawing DXF (URL):	https://ideelectric.com/docs/plans/dxf/GNG403020.dxf
Product drawing (PDF):	https://ideelectric.com/docs/plans/pdf/GNG403020.pdf
Assembly instructions:	https://assemblysteps.org/qr/92890