Ref: GPS4PT

Serie Gold-P surface

IP40 Surface plastic boxes

IP40 surface distribution box 1x4 modules. Transparent door



Features

Application:	Tertiary (residential)
Suitable for outdoor installation:	No
Type of installation:	Surface
Material Quality:	ABS

Modular capacity

Capacity/Number of modules:	04
Number of rows:	1x4

Technical data

Protection degree:	IP40
Resistance to impact:	IK08
Glow wire resistance (ºC):	650
Double insulation:	Class I

Dimensions

Piece dimensions - HxWxD (mm):	202.6 x 140 x 97.6

Additional features

Door/window/lid type:	Transparent
Reversible door:	Yes
UV protection:	No
Number of doors:	1
Lock type:	Snap closure

Ref: GPS4PT

No. of locks:	1
Lock - Key Type:	Without key. Possibility of lock with key as accessory (ref. 22015)
Sealable:	No
Linkable:	No
Neutral and earth bars:	No
Includes DIN Rail:	Yes
Plate:	No
Adjustable Plate:	No
Perforated Plate:	No

Materials

Halogen-free materials:	Yes
Body/Base Material:	ABS
Door/Lid/Window Material:	Polycarbonate (PC)
Chassis cover material:	ABS
Lock material:	ABS
Base color:	White RAL 9003
Door color:	Smoked

Ref: GPS4PT

Electrical properties

Maximum voltage (V):	1000 AC / 1500 DC

Packaging

Supply:	Supplied in individual packaging When several items are sent together, they are bundled together with transparent film Supplied with all the elements assembled, except for the elements supplied in the accessory bag **Accessory bag:** Screws for frame-base closure Door hinges Cover for white modules (6 modules) Hermetic caps Level Module identification strips
Individual Packaging Type:	Box
UoM Packaging - Individual:	Unit
Minimum Selling Quantity:	5
Individual packaging dimensions - HxWxD (m):	0.213 x 0.146 x 0.108
Net weight per unit (kg):	0.524
Gross weight per unit (kg):	0.576

Codes

GTIN-13 code:	8431044602417
Tariff code:	85381000
ETIM code 9.0:	EC000214

Downloads (links)

Assembly instructions:	https://assemblysteps.org/qr/91214