Ref: IA2C2510

Serie Circuit breakers: protection system

Protection System

Automatic switch 2P 25AC 10KA 230/400V 50/60HZ compatible with accessories



Features

Product Type:	Sistema de protección magnetotérmica
Poles:	2P
Curve:	C
Rated Current - In(A):	25
Rated short-circuit breaking capacity (Icn):	10
Piece dimensions - HxWxD (mm):	87 x 36 x 78

Electrical specifications

Rated frequency (Hz):	50/60
Rated operating voltage - Ue (V):	400
Rated Insulation Voltage - Ui (V):	500
Maximum Working Voltage - Umax (V):	440
Dielectric Test Voltage (kV):	2
Mechanical Durability (Cycles):	10000
Electrical Durability (Cycles):	6000

Connection and installations

Ambient temperature (with daily average ≤ 35 ºC) (ºC):	-5 / +40
Reference temperature for thermal element adjustment (ºC):	30
Storage temperature (ºC):	-25 / +70
Degree of protection of connection terminal:	IP40
Cable (mm²):	25
Fixing method:	DIN rail

Ref: IA2C2510

Pollution degree:	2
Tightening torque (Nm):	3
Connection:	Top and bottom

Additional features

Degree of protection of enclosure:	IP20
Selective protection:	No
Switch-off delay:	No
With locking device:	No
Additional Equipment:	No
Explosion-proof:	No
Suitable for outdoor installation:	No

Materials

Halogen-free materials:	No

Certificates and regulations

Standards:	EN 60898-1

Packaging

Individual Packaging Type:	Uncaged
UoM Packaging - Individual:	Unit
Minimum Selling Quantity:	1
Individual packaging dimensions - HxWxD (m):	0.087 x 0.036 x 0.078
Net weight per unit (kg):	0.212
Gross weight per unit (kg):	0.233

Codes

GTIN-13 code:	8431044966823
Tariff code:	8536201090
ETIM code 9.0:	EC000042