Ref: INXT504020

Serie Argenta Inox

IP66 Stainless steel cabinets

IP66 stainless steel 304L wall-cabinet 500x400x200. Transparent door with plate



Features

Application:	Corrosive environments,Food industry
Suitable for outdoor installation:	No
Type of installation:	Wall-mounted
Piece dimensions - HxWxD (mm):	500 x 400 x 200
Material Quality:	AISI 304 stainless steel

Technical data

Protection degree:	IP66
NEMA degree of protection:	1, 4, 4x, 12
Resistance to impact:	IK09

Dimensions

Piece dimensions - HxWxD (mm):	500 x 400 x 200
Plate dimensions - HxW (mm):	470 x 350
Wall Mounting - HxW (mm):	460 x 360
Usable interior space - HxWxD (mm):	450 x 350 x 179
Glass door visible area - HxW (mm):	396 x 248

Ref: INXT504020

Additional features

Door/window/lid type:	Single transparent
Reversible door:	Yes
Number of doors:	1
Body type:	Compact
Lock type:	5-mm double-bit
Plate:	Yes
Plate Type:	Smooth
Adjustable Plate:	No
Perforated Plate:	No
No. of hinges:	2
No. of locks:	2x1P
Lock - Key Type:	5 mm double-bit Zamak key included
No. of door profiles:	2

Materials

Door/Lid/Window Material:	Tempered glass
Lock material:	Zamak insert, cam and housing
Plate material:	Galvanised steel
Gasket material:	Polyurethane
Finish:	Scotch 320 satin finish
Body thickness (mm):	1.2
Door thickness (mm):	1.2
Plate thickness (mm):	2

Ref: INXT504020

Maximum loads

Maximum total load (kg):	225
Maximum door load (kg):	25
Maximum plate load (kg):	200

Electrical properties

Maximum voltage (V): 1000 AC / 1500 DC

Power dissipation:

Power dissipation P(W) as a function of temperature increase ΔT (°C)				
20	25	30	35	40
62.9	78.7	94.4	110.1	125.8

Data calculated according to IEC TR 60890 using the method for verifying temperature rise in low-voltage switchgear and controlgear assemblies.

Certificates and regulations

Directive:	2014/35/EU
Standards:	UNE-EN 62208,UNE-EN 61439-1

Packaging

Supply:

Supplied in individual packaging containing cabinet, plate and accessory bag
The cabinets are supplied with protective film
Mounting plate:
For cabinets with a height ≤700 mm and width 800 mm are supplied unassembled in the packaging
For cabinets with a height ≤700 mm and width ≥800 mm are supplied assembled
For cabinets with a height >700 mm are supplied assembled
Accessory bag:
4 watertight caps (if the wall-mounting cut-out holes are not used)
Earth kit consisting of nut, washer and earth symbol label
Plate height adjusters and nuts
5 mm double-bit key

Individual Packaging Type:	Box
UoM Packaging - Individual:	Unit
Minimum Selling Quantity:	1
Individual packaging dimensions - HxWxD (m):	0.52 x 0.415 x 0.22
Net weight per unit (kg):	11.953
Gross weight per unit (kg):	13.148

Codes

Ref: INXT504020

GTIN-13 code:	8431044223308
Tariff code:	85381000
ETIM code 9.0:	EC000261

Downloads (links)

Product drawing STP (URL):	https://ideelectric.com/docs/plans/stp/INXT504020.stp
Product drawing (PDF):	https://ideelectric.com/docs/plans/pdf/INXT504020.pdf
Assembly instructions:	https://assemblysteps.org/qr/92890_1