**Ref: INXT604020-316**

# Serie Argenta Inox

## IP66 Stainless steel cabinets

IP66 stainless steel 316L wall-cabinet 600x400x200. Transparent door with plate



## Features

| | |
|---|---|
| **Application:** | Corrosive environments,Food industry |
| **Suitable for outdoor installation:** | No |
| **Type of installation:** | Wall-mounted |
| **Piece dimensions - HxWxD (mm):** | 600 x 400 x 200 |
| **Material Quality:** | AISI 316 stainless steel |

## Technical data

| | |
|---|---|
| **Protection degree:** | IP66 |
| **NEMA degree of protection:** | 1, 4, 4x, 12 |
| **Resistance to impact:** | IK09 |

## Dimensions

| | |
|---|---|
| **Piece dimensions - HxWxD (mm):** | 600 x 400 x 200 |
| **Plate dimensions - HxW (mm):** | 570 x 350 |
| **Wall Mounting - HxW (mm):** | 560 x 360 |
| **Usable interior space - HxWxD (mm):** | 550 x 350 x 179 |
| **Glass door visible area - HxW (mm):** | 496 x 248 |

## Ref: INXT604020-316

### Additional features

| | |
|---|---|
| **Door/window/lid type:** | Single transparent |
| **Reversible door:** | Yes |
| **Number of doors:** | 1 |
| **Body type:** | Compact |
| **Lock type:** | 5-mm double-bit |
| **Plate:** | Yes |
| **Plate Type:** | Smooth |
| **Adjustable Plate:** | No |
| **Perforated Plate:** | No |
| **No. of hinges:** | 2 |
| **No. of locks:** | 2x1P |
| **Lock - Key Type:** | 5 mm double-bit Zamak key included |
| **No. of door profiles:** | 2 |

### Materials

| | |
|---|---|
| **Door/Lid/Window Material:** | Tempered glass |
| **Lock material:** | Zamak insert, cam and housing |
| **Plate material:** | Galvanised steel |
| **Gasket material:** | Polyurethane |
| **Finish:** | Scotch 320 satin finish |
| **Body thickness (mm):** | 1.2 |
| **Door thickness (mm):** | 1.2 |
| **Plate thickness (mm):** | 2 |

## Ref: INXT604020-316

## Maximum loads

| | |
|---|---|
| **Maximum total load (kg):** | 225 |
| **Maximum door load (kg):** | 25 |
| **Maximum plate load (kg):** | 200 |

## Electrical properties

**Maximum voltage (V):** 1000 AC / 1500 DC

**Power dissipation:**

| Power dissipation P(W) as a function of temperature increase ΔT (°C) | | | | |
|---|---|---|---|---|
| 20 | 25 | 30 | 35 | 40 |
| 73.0 | 91.3 | 109.6 | 127.8 | 146.1 |

Data calculated according to IEC TR 60890 using the method for verifying temperature rise in low-voltage switchgear and controlgear assemblies.

## Certificates and regulations

| | |
|---|---|
| **Directive:** | 2014/35/EU |
| **Standards:** | UNE-EN 62208,UNE-EN 61439-1 |

## Packaging

**Supply:**

Supplied in individual packaging containing cabinet, plate and accessory bag
The cabinets are supplied with protective film
**Mounting plate:**
For cabinets with a height ≤700 mm and width 800 mm are supplied unassembled in the packaging
For cabinets with a height ≤700 mm and width ≥800 mm are supplied assembled
For cabinets with a height >700 mm are supplied assembled
**Accessory bag:**
4 watertight caps (if the wall-mounting cut-out holes are not used)
Earth kit consisting of nut, washer and earth symbol label
Plate height adjusters and nuts
5 mm double-bit key

| | |
|---|---|
| **Individual Packaging Type:** | Box |
| **UoM Packaging - Individual:** | Unit |
| **Minimum Selling Quantity:** | 1 |
| **Individual packaging dimensions - HxWxD (m):** | 0.62 x 0.415 x 0.22 |
| **Net weight per unit (kg):** | 14.908 |
| **Gross weight per unit (kg):** | 16.399 |

## Codes

## Ref: INXT604020-316

| | |
|---|---|
| **GTIN-13 code:** | 8431044226910 |
| **Tariff code:** | 85381000 |
| **ETIM code 9.0:** | EC000261 |

## Downloads (links)

| | |
|---|---|
| **Product drawing STP (URL):** | https://ideelectric.com/docs/plans/stp/INXT604020-316.stp |
| **Product drawing (PDF):** | https://ideelectric.com/docs/plans/pdf/INXT604020-316.pdf |
| **Assembly instructions:** | https://assemblysteps.org/qr/92890_1 |