**Ref: IS1125**

# Serie Circuit breakers: management systems

## Management systems

Disconnector 125A 1P



## Features

| | |
|---|---|
| **Application:** | Industrial |
| **Product Type:** | Interruptor seccionador |
| **Rated short-circuit making capacity - Icm (A):** | 2500 |
| **Pollution degree:** | 2 |
| **Terminal connection type:** | Cable/connection combs |
| **Rated short-time withstand current – Icw 1 s:** | 12 x In |
| **Utilization category:** | AC-22A |
| **Top/bottom connectable conductor cross-section (mm²):** | 16-50 |
| **Connection:** | Top and bottom |
| **Rated impulse withstand voltage - Uimp (kV):** | 6 |
| **Poles:** | 1P |
| **Rated Current - In(A):** | 125 |
| **Rated operating voltage - Ue (V):** | 230 |
| **Rated Insulation Voltage - Ui (V):** | 500 |
| **Rated frequency (Hz):** | 50/60 |
| **Electrical durability (cycles):** | 4000 |
| **Mechanical durability (cycles):** | 10000 |
| **Protection degree:** | IP20 |
| **Suitable for outdoor installation:** | No |

## Certificates and regulations

| | |
|---|---|
| **Standards:** | EN 60947-3 |

## Ref: IS1125

### Packaging

| | |
|---|---|
| **Individual Packaging Type:** | Uncaged |
| **UoM Packaging - Individual:** | Unit |
| **Minimum Selling Quantity:** | 1 |
| **Individual packaging dimensions - HxWxD (m):** | 0.084 x 0.018 x 0.078 |
| **Net weight per unit (kg):** | 0.075 |
| **Gross weight per unit (kg):** | 0.083 |

### Codes

| | |
|---|---|
| **GTIN-13 code:** | 8431044494579 |
| **Tariff code:** | 8536201090 |
| **ETIM code 9.0:** | EC000216 |

### Downloads (Links)

| | |
|---|---|
| **Assembly instructions:** | https://assemblysteps.org/qr/ |