Ref: IS2100

Serie Circuit breakers: management systems

Management systems

Disconnector 100A 2P



Features

Application:	Industrial
Product Type:	Interruptor seccionador
Rated short-circuit making capacity - Icm (A):	2500
Pollution degree:	2
Terminal connection type:	Cable/connection combs
Rated short-time withstand current – Icw 1 s:	12 x In
Utilization category:	AC-22A
Top/bottom connectable conductor cross-section (mm²):	16-50
Connection:	Top and bottom
Rated impulse withstand voltage - Uimp (kV):	6
Poles:	2P
Rated Current - In(A):	100
Rated operating voltage - Ue (V):	400
Rated Insulation Voltage - Ui (V):	500
Rated frequency (Hz):	50/60
Electrical durability (cycles):	4000
Mechanical durability (cycles):	10000
Protection degree:	IP20
Suitable for outdoor installation:	No

Certificates and regulations

Standards:	EN 60947-3

Ref: IS2100

Packaging

Individual Packaging Type:	Uncaged
UoM Packaging - Individual:	Unit
Minimum Selling Quantity:	1
Individual packaging dimensions - HxWxD (m):	0.084 x 0.035 x 0.078
Net weight per unit (kg):	0.15
Gross weight per unit (kg):	0.165

Codes

GTIN-13 code:	8431044491721
Tariff code:	8536201090
ETIM code 9.0:	EC000216

Downloads (Links)

Assembly instructions:	https://assemblysteps.org/qr/