**Ref: POL12510042**

# Serie Glass

## IP66-IP55 Polyester cabinets

IP55 polyester wall cabinet 1250x1000x420. Double opaque door with handle



## Features

| | |
|---|---|
| **Application:** | Automation and control,Corrosive environments,Renewable energies |
| **Suitable for outdoor installation:** | Yes |
| **Type of installation:** | Wall-mounted |
| **Piece dimensions - HxWxD (mm):** | 1260 x 1000 x 420 |
| **Material Quality:** | Glass-reinforced polyester |

## Technical data

| | |
|---|---|
| **Protection degree:** | IP55 |
| **Resistance to impact:** | IK10 |
| **Double insulation:** | Class II |
| **Thermal class (ºC):** | 105 ºC (A) |

## Dimensions

| | |
|---|---|
| **Piece dimensions - HxWxD (mm):** | 1260 x 1000 x 420 |
| **Wall Mounting - HxW (mm):** | 1118 x 1052 |
| **Usable interior space - HxWxD (mm):** | 1162 x 905 x 382 |

## Ref: POL12510042

### Additional features

| | |
|---|---|
| **Door/window/lid type:** | Double opaque |
| **Reversible door:** | No |
| **Number of doors:** | 2 |
| **Body type:** | Compact |
| **Lock type:** | 3-mm double-bit handle |
| **Plate:** | No |
| **Adjustable Plate:** | No |
| **Perforated Plate:** | No |
| **No. of hinges:** | 8 |
| **No. of locks:** | 2x3P |
| **Lock - Key Type:** | 3 mm double-bit Key included |

### Materials

| | |
|---|---|
| **Lock material:** | Black polyamide housing |
| **Gasket material:** | Polyurethane |
| **Color:** | Grey RAL 7035 |
| **Door thickness (mm):** | 3.5 |
| **Top/bottom panel thickness (mm):** | 3 |
| **Back panel thickness (mm):** | 3.5 |
| **Rear door thickness (mm):** | 3.5 |
| **Side thickness (mm):** | 3 |

## Ref: POL12510042

### Maximum loads

| | |
|---|---|
| **Maximum door load (kg):** | 19 |
| **Maximum plate load (kg):** | 259 |

### Electrical properties

| | |
|---|---|
| **Maximum voltage (V):** | 1000 AC / 1500 DC |
| **Glow wire resistance (ºC):** | 960 |

**Power dissipation:**

| Power dissipation P(W) as a function of temperature increase ΔT (°C) | | | | |
|---|---|---|---|---|
| 20 | 25 | 30 | 35 | 40 |
| 205.0 | 271.0 | 341.0 | 413.0 | 488.0 |

Data calculated according to IEC TR 60890 using the method for verifying temperature rise in low-voltage switchgear and controlgear assemblies.

### Certificates and regulations

| | |
|---|---|
| **Directive:** | 2014/35/EU |
| **Standards:** | UNE-EN 62208,UNE-EN 61439-1 |

### Packaging

| | |
|---|---|
| **Supply:** | **IP66 cabinets (from a height of 300 mm to 800 mm**)<br>Supplied in individual packaging<br>The accessories for fitting the mounting plate are fitted on the cabinet. Plate supplied in individual packaging if requested as an accessory<br>Key<br>**IP55 cabinets (from a height of 500 mm to 1250 mm)**<br>Supplied individually shrink-wrapped and protected with cardboard at top and bottom<br>The accessories for fitting the mounting plate are fitted on the cabinet. Plate supplied in individual packaging if requested as an accessory<br>Key |
| **Individual Packaging Type:** | Wrap |
| **UoM Packaging - Individual:** | Unit |
| **Minimum Selling Quantity:** | 1 |
| **Individual packaging dimensions - HxWxD (m):** | 1.26 x 1 x 0.42 |
| **Net weight per unit (kg):** | 36.81 |
| **Gross weight per unit (kg):** | 40.491 |

### Codes

| | |
|---|---|
| **GTIN-13 code:** | 8431044243993 |

## Ref: POL12510042

| | |
|---|---|
| **Tariff code:** | 85381000 |
| **ETIM code 9.0:** | EC000261 |

## Downloads (links)

| | |
|---|---|
| **Product drawing STP (URL):** | https://ideelectric.com/docs/plans/stp/POL12510042.stp |
| **Product drawing DXF (URL):** | https://ideelectric.com/docs/plans/dxf/POL12510042.dxf |
| **Product drawing (PDF):** | https://ideelectric.com/docs/plans/pdf/POL12510042.pdf |
| **Assembly instructions:** | https://assemblysteps.org/qr/ |