Ref: V2GL2/67

Serie Pryma Complet

IP67 Boxes with power sockets

IP67 box with power sockets 1x13 mod. (1712GM). Without protections



Features

Application:	Industrial (watertight and distribution enclosures),Construction
Suitable for outdoor installation:	Yes
Type of installation:	Surface
Material Quality:	ABS

Modular capacity

Box mounting:	1712M
Capacity/Number of modules:	13
Number of rows:	1x13

Components:

Nº	Description	IP	Poles	Current (A)	Voltage (V)
3	Sloping flush-fit sockets	67	2P+E	16	230
3	Sloping flush-fit sockets	67	3P+E	32	400

Technical data

Protection degree:	IP67
Resistance to impact:	IK08
Glow wire resistance (ºC):	650
Glow-wire resistance of enclosure (°C):	650
Ball pressure test on enclosure (°C):	70
Ball pressure in sockets (ºC):	125
Double insulation:	Class II

Dimensions

Piece dimensions - HxWxD (mm):	504 x 297 x 235

Ref: V2GL2/67

Additional features

Emergency mushroom push button:	No
Door/window/lid type:	Transparent
Door/lid/window fastening:	Screw-on
Reversible door:	No
UV protection:	Yes
Lock type:	With screws
Sealable:	Yes
Linkable:	No
Includes DIN Rail:	Yes

Materials

Halogen-free materials:	Yes
Body/Base Material:	ABS
Frame material:	ABS
Door/Lid/Window Material:	Polycarbonate (PC)
Color:	Grey RAL 7035
Door color:	Smoked

Electrical properties

Maximum voltage (V):	1000 AC / 1500 DC

Ref: V2GL2/67

Certificates and regulations

Directive:	2014/35/EU
Standards:	UNE-EN 62208,UNE-EN 61439-1

Packaging

Supply:	Supplied fully assembled according to the specifications of each reference, protected with shrink wrap and packed in multiple cardboard packaging according to the number of units ordered With certificate of conformity, description, number of socket outlets and protection devices, and the corresponding single-line diagram
Individual Packaging Type:	Box
UoM Packaging - Individual:	Unit
Minimum Selling Quantity:	1
Individual packaging dimensions - HxWxD (m):	0.525 x 0.315 x 0.275
Net weight per unit (kg):	4.777
Gross weight per unit (kg):	5.255

Codes

GTIN-13 code:	8431044235189
Tariff code:	85371098
ETIM code 9.0:	EC000379

Downloads (links)

Assembly instructions:	https://assemblysteps.org/qr/