Ref: VF113DC

Serie Ventilation

Ventilation

Fan with filter 113 m³/h 24V DC IP54



Features

Suitable for outdoor installation:	No
Product Type:	Filter fan (DC)

Additional features

Relative humidity range (%):	0-95
Electrical connection:	Terminal
Fixing method:	Quick (click/press fixing)

Ventilation

Voltage (V):	24
Air flow with filter (m3/h):	113
Operating temperature (ºC):	-20/+65
Filtering efficiency (%):	≤ 73
Service life at 40 °C (h):	50
Noise Level (dB):	35
Current Consumption (A):	0,31
Power consumption (W):	7.44
Static Pressure (Pa):	38
Overcurrent protection:	Impedancia
Flow direction:	De fuera hacia dentro
Reversible:	Yes
Bearing:	Ball bearing

Technical data

Ref: VF113DC

Protection degree:	IP54

Materials

Material Quality:	ABS
Filter:	Yes
Filter Material (g/m3):	Nylon fibre 150
Gasket material:	Polyurethane
Halogen-free materials:	No
Color:	Grey RAL 7035

Dimensions

Piece dimensions - HxWxD (mm):	148.5 x 148.5 x 68.5
Cut-out dimensions (mm):	124 x 124
Wall thickness (mm):	2

Certificates and regulations

Directive:	2014/35/EU
Standards:	IEC 62208; IEC 61439-1

Packaging

Supply:	Supplied in individual cardboard packaging
Individual Packaging Type:	Box
UoM Packaging - Individual:	Unit
Minimum Selling Quantity:	1
Individual packaging dimensions - HxWxD (m):	0.149 x 0.149 x 0.069
Net weight per unit (kg):	0.478
Gross weight per unit (kg):	0.526

Codes

GTIN-13 code:	8431044250342
Tariff code:	84145995
ETIM code 9.0:	EC000320

Ref: VF113DC

Downloads (Links)

Product drawing STP (URL):	https://ideelectric.com/docs/plans/stp/VF113DC.stp
Product drawing DXF (URL):	https://ideelectric.com/docs/plans/dxf/VF113DC.dxf
Product drawing (PDF):	https://ideelectric.com/docs/plans/pdf/VF113DC.pdf
Product drawing EDZ (URL):	https://ideelectric.com/docs/plans/edz/IDE.VF113DC.edz
Assembly instructions:	https://assemblysteps.org/qr/93061