Ref: VF637AC

Serie Ventilation

Ventilation

Fan with filter 637 m³/h 230V AC IP54



Features

Suitable for outdoor installation:	No
Product Type:	Filter fan (AC)

Additional features

Relative humidity range (%):	0-95
Electrical connection:	Terminal
Fixing method:	Quick (click/press fixing)

Ventilation

Voltage (V):	230
Frequency (Hz):	50-60
Air flow with filter (m3/h):	637-707
Operating temperature (ºC):	-20/+75
Filtering efficiency (%):	≤ 73
Service life at 40 °C (h):	50
Noise Level (dB):	55
Current Consumption (A):	0,30-0,34
Power consumption (W):	65
Static Pressure (Pa):	78-90
Overcurrent protection:	Térmica
Flow direction:	De fuera hacia dentro
Reversible:	Yes
Bearing:	Ball bearing

Ref: VF637AC

Technical data

Protection degree:	IP54

Materials

Material Quality:	ABS
Filter:	Yes
Filter Material (g/m3):	Nylon fibre 150
Gasket material:	Polyurethane
Halogen-free materials:	No
Color:	Grey RAL 7035

Dimensions

Piece dimensions - HxWxD (mm):	324 x 324 x 145
Cut-out dimensions (mm):	292 x 292
Wall thickness (mm):	2

Certificates and regulations

Directive:	2014/35/EU
Standards:	IEC 62208; IEC 61439-1

Packaging

Supply:	Supplied in individual cardboard packaging
Individual Packaging Type:	Box
UoM Packaging - Individual:	Unit
Minimum Selling Quantity:	1
Individual packaging dimensions - HxWxD (m):	0.324 x 0.324 x 0.145
Net weight per unit (kg):	3.43
Gross weight per unit (kg):	3.773

Codes

GTIN-13 code:	8431044250205

Ref: VF637AC

Tariff code:	84145995
ETIM code 9.0:	EC000320

Downloads (Links)

Product drawing STP (URL):	https://ideelectric.com/docs/plans/stp/VF637AC.stp
Product drawing DXF (URL):	https://ideelectric.com/docs/plans/dxf/VF637AC.dxf
Product drawing (PDF):	https://ideelectric.com/docs/plans/pdf/VF637AC.pdf
Product drawing EDZ (URL):	https://ideelectric.com/docs/plans/edz/IDE.VF637AC.edz
Assembly instructions:	https://assemblysteps.org/qr/93061