Ref: VT730

Serie Ventilation

Ventilation

Ceiling fan 730 m³/h 230V AC IP54



Features

Suitable for outdoor installation:	No

Additional features

Relative humidity range (%):	0-95
Electrical connection:	Cable
Fixing method:	With screws

Ventilation

Voltage (V):	230
Frequency (Hz):	50-60
Air flow with filter (m3/h):	730-830
Operating temperature (ºC):	-30/+80
Service life at 40 °C (h):	50
Noise Level (dB):	60
Current Consumption (A):	0,46-0,51
Power consumption (W):	98
Static Pressure (Pa):	300-440
Overcurrent protection:	Térmica
Flow direction:	De dentro hacia fuera
Reversible:	No
Bearing:	Ball bearing

Technical data

Protection degree:	IP54

Ref: VT730

Materials

Material Quality:	ABS,Iron
Filter:	No
Gasket material:	Polyurethane
Halogen-free materials:	No
Color:	Grey RAL 7035

Dimensions

Piece dimensions - HxWxD (mm):	310 x 310 x 140
Cut-out dimensions (mm):	Ø220

Certificates and regulations

Directive:	2014/35/EU
Standards:	IEC 62208; IEC 61439-1

Packaging

Supply:	Supplied in individual cardboard packaging
Individual Packaging Type:	Box
UoM Packaging - Individual:	Unit
Minimum Selling Quantity:	1
Individual packaging dimensions - HxWxD (m):	0.31 x 0.31 x 0.14
Net weight per unit (kg):	5.234
Gross weight per unit (kg):	5.757

Codes

GTIN-13 code:	8431044250373
Tariff code:	84145995
ETIM code 9.0:	EC000320

Downloads (Links)

Product drawing STP (URL):	https://ideelectric.com/docs/plans/stp/VT730.stp

Ref: VT730

Product drawing DXF (URL):	https://ideelectric.com/docs/plans/dxf/VT730.dxf
Product drawing (PDF):	https://ideelectric.com/docs/plans/pdf/VT730.pdf
Product drawing EDZ (URL):	https://ideelectric.com/docs/plans/edz/IDE.VT730.edz
Assembly instructions:	https://assemblysteps.org/qr/93062